



Hibernate Annotations

Reference Guide

Version: 3.1 beta 7

Table of Contents

Preface	iv
1. Setting up an annotations project	1
1.1. Requirements	1
1.2. Configuration	1
2. Entity Beans	3
2.1. Intro	3
2.2. Mapping with EJB3 Annotations	3
2.2.1. Declaring an entity bean	3
2.2.1.1. Defining the table	4
2.2.1.2. Versioning for optimistic locking	4
2.2.2. Mapping simple properties	4
2.2.2.1. Declaring basic property mappings	4
2.2.2.2. Declaring column attributes	5
2.2.2.3. Embedded objects (aka components)	6
2.2.2.4. Non-annotated property defaults	8
2.2.3. Mapping identifier properties	8
2.2.4. Mapping inheritance	10
2.2.4.1. Table per class	11
2.2.4.2. Single table per class hierarchy	11
2.2.4.3. Joined subclasses	12
2.2.4.4. Inherit properties from superclasses	12
2.2.5. Mapping entity bean associations/relationships	13
2.2.5.1. One-to-one	13
2.2.5.2. Many-to-one	14
2.2.5.3. Collections	15
2.2.5.4. Transitive persistence with cascading	20
2.2.5.5. Association fetching	20
2.2.6. Mapping composite primary and foreign keys	21
2.2.7. Mapping secondary tables	22
2.3. Mapping Queries	23
2.3.1. Mapping EJBQL/HQL queries	23
2.3.2. Mapping native queries	23
2.4. Hibernate Annotation Extensions	24
2.4.1. Entity	25
2.4.2. Identifier	26
2.4.3. Property	26
2.4.3.1. Formula	26
2.4.3.2. Type	26
2.4.3.3. Index	27
2.4.4. Inheritance	27
2.4.5. Association related annotations	28
2.4.6. Collection related annotations	28
2.4.6.1. Parameter annotations	28
2.4.6.2. Extra collection types	29
2.4.7. Cache	30
2.4.8. Filters	31
2.4.9. Queries	31
3. Hibernate Validator	33

3.1. Constraints	33
3.1.1. What is a constraint?	33
3.1.2. Built in constraints	33
3.1.3. Error messages	34
3.1.4. Writing your own constraints	35
3.1.5. Annotating your domain model	36
3.2. Using the Validator framework	37
3.2.1. Database schema-level validation	37
3.2.2. Hibernate event-based validation	37
3.2.3. Application-level validation	38
3.2.4. Validation informations	38
4. Hibernate Lucene Integration	40
4.1. Using Lucene to index your entities	40
4.1.1. Annotating your domain model	40
4.1.2. Enabling automatic indexing	40
A. Compliance and limitations	42

Preface

Hibernate, like all other object/relational mapping tools, requires metadata that governs the transformation of data from one representation to the other (and vice versa). In Hibernate 2.x, mapping metadata is most of the time declared in XML text files. Another option is XDoclet, utilizing Javadoc source code annotations and a preprocessor at compile time. The same kind of annotation support is now available in the standard JDK, although more powerful and better supported by tools. IntelliJ IDEA, and Eclipse for example, support auto-completion and syntax highlighting of JDK 5.0 annotations. Annotations are compiled into the bytecode and read at runtime (in Hibernate's case on startup) using reflection, so no external XML files are needed.

The EJB3 specification recognizes the interest and the success of the transparent object/relational mapping paradigm. The EJB3 specification standardizes the basic APIs and the metadata needed for any object/relational persistence mechanism. *Hibernate EntityManager* implements the programming interfaces and lifecycle rules as defined by the EJB3 persistence specification. Together with *Hibernate Annotations*, this wrapper implements a complete (and standalone) EJB3 persistence solution on top of the mature Hibernate core. You may use a combination of all three together, annotations without EJB3 programming interfaces and lifecycle, or even pure native Hibernate, depending on the business and technical needs of your project. You can at all times fall back to Hibernate native APIs, or if required, even to native JDBC and SQL.

Please note that this documentation is based on a preview release of the Hibernate Annotations that follows the public draft of EJB 3.0/JSR-220 persistence annotations. This work is already very close to the final concepts in the new specification. Our goal is to provide a complete set of ORM annotations, including EJB3 standard annotations as well as Hibernate3 extensions for cases not covered by the specification. Eventually you will be able to create all possible mappings with annotations. See the Appendix A, *Compliance and limitations* section for more information.

Chapter 1. Setting up an annotations project

1.1. Requirements

- Download and unpack the Hibernate Annotations distribution from the Hibernate website.
- *This preview release requires Hibernate 3.1. Do not use this release of Hibernate Annotations with an older version of Hibernate 3.x!*
- This release is known to work on Hibernate core 3.1.0
- Make sure you have JDK 5.0 installed. You can of course continue using XDoclet and get some of the benefits of annotation-based metadata with older JDK versions. Note that this document only describes JDK 5.0 annotations and you have to refer to the XDoclet documentation for more information.

1.2. Configuration

First, set up your classpath (after you have created a new project in your favorite IDE):

- Copy all Hibernate3 core and required 3rd party library files (see lib/README.txt in Hibernate).
- Copy `hibernate-annotations.jar` and `lib/ejb3-persistence.jar` from the Hibernate Annotations distribution to your classpath as well.

We also recommend a small wrapper class to startup Hibernate in a static initializer block, known as `HibernateUtil`. You might have seen this class in various forms in other areas of the Hibernate documentation. For Annotation support you have to enhance this helper class as follows:

```
package hello;

import org.hibernate.*;
import org.hibernate.cfg.*;
import test.*;
import test.animals.Dog;

public class HibernateUtil {

    private static final SessionFactory sessionFactory;

    static {
        try {

            sessionFactory = new AnnotationConfiguration()
                .addPackage("test.animals") //the fully qualified package name
                .addAnnotatedClass(Flight.class)
                .addAnnotatedClass(Sky.class)
                .addAnnotatedClass(Person.class)
                .addAnnotatedClass(Dog.class)
                .buildSessionFactory();

        } catch (Throwable ex) {
            // Log exception!
            throw new ExceptionInInitializerError(ex);
        }
    }

    public static Session getSession()
        throws HibernateException {
```

```
        return sessionFactory.openSession();
    }
}
```

Interesting here is the use of `AnnotationConfiguration` and the declaration of a package and persistent classes.

Alternatively, you can declare your annotated packages and classes in your regular XML configuration file (usually `hibernate.cfg.xml`). Here is the equivalent of the above declaration:

```
<!DOCTYPE hibernate-configuration PUBLIC
"-//Hibernate/Hibernate Configuration DTD 3.0//EN"
"http://hibernate.sourceforge.net/hibernate-configuration-3.0.dtd">

<hibernate-configuration>
  <session-factory>
    <mapping package="test.animals"/>
    <mapping class="test.Flight"/>
    <mapping class="test.Sky"/>
    <mapping class="test.Person"/>
    <mapping class="test.animals.Dog"/>
  </session-factory>
</hibernate-configuration>
```

This kind of configuration is certainly a preferred way. Note that you can mix the `hbm.xml` use and the new annotation one. Note that you have to use an `AnnotationConfiguration` to startup Hibernate with annotation support, even if you use externalized settings.

You can also use the Hibernate Entity Manager which has it's own configuration mechanism. Please refer to this project documentation for more details.

There is no other difference in the way you use Hibernate APIs with annotations, expect for this change in the startup routine or in the configuration file. You can use your favorite configuration method for other properties (`hibernate.properties`, `hibernate.cfg.xml`, programmatic APIs, etc). You can even mix annotated persistent classes and classic `hbm.cfg.xml` declarations with the same `SessionFactory`. You can however not declare a class several times (whether annotated or through `hbm.xml`). You cannot mix configuration strategies (`hbm` vs annotations) in a mapped entity hierarchy either.

To ease the migration process from `hbm` files to annotations, the configuration mechanism detects the mapping duplication between annotations and `hbm` files. HBM files are then prioritized over annotated metadata on a class to class basis. You can change the priority using `hibernate.mapping.precedence` property. The default is `hbm`, `class`, changing it to `class`, `hbm` will prioritize the annotated classes over `hbm` files when a conflict occurs.

Chapter 2. Entity Beans

2.1. Intro

This section covers EJB 3.0 entity bean annotations and Hibernate-specific extensions.

2.2. Mapping with EJB3 Annotations

EJB3 entity beans are plain POJOs. Actually they represent the exact same concept as the Hibernate persistent entities. Their mappings are defined through JDK 5.0 annotations (an XML descriptor syntax for overriding will be defined in the EJB3 specification, but it's not finalized so far). Annotations come in two categories, the logical mapping annotations (allowing you to describe the object model, the class associations, etc.) and the physical mapping annotations (describing the physical schema, tables, columns, indexes, etc). We will mix annotations from both categories in the following code examples.

Annotations are in the `javax.persistence.*` package. We recommend an IDE that can autocomplete annotation interfaces and attributes for you.

For more and runnable concrete examples read the JBoss EJB 3.0 tutorial or review the Hibernate Annotations test suite. Most of the unit tests have been designed to represent a concrete example.

2.2.1. Declaring an entity bean

Every bound persistent POJO class is an entity bean and is declared using the `@Entity` annotation (at the class level):

```
@Entity
public class Flight implements Serializable {
    Long id;

    @Id
    public Long getId() { return id; }

    public setId(Long id) { this.id = id; }
}
```

`@Entity` declares the class as an entity bean (i.e. a persistent POJO class), `@Id` declares the identifier property of this entity bean. The other mapping declarations are implicit. This configuration by exception concept is central to the new EJB3 specification and a major improvement. The class `Flight` is mapped to the `Flight` table, using the column `id` as its primary key column.

The `@Entity` annotation allows you to define whether an entity bean should be accessed through its getters/setters methods (default) or whether the entity manager should access the fields of the given entity directly:

```
@Entity(access = AccessType.PROPERTY)
or
@Entity(access = AccessType.FIELD)
```

The EJB3 spec requires that you declare annotations on the element that will be used, i.e. the getter method if

you use `PROPERTY` access, the field if you use `FIELD` access.

Defining the table

`@Table` is set at the class level; it allows you to define the table, catalog, and schema names for your entity bean mapping. If no `@Table` is defined the default values are used: the unqualified class name of the entity.

```
@Entity(access=AccessType.FIELD)
@Table(name="tbl_sky")
public class Sky implements Serializable {
    ...
}
```

The `@Table` element also contains a `schema` and a `catalog` attributes, if they need to be defined. You can also define unique constraints to the table using the `@UniqueConstraint` annotation in conjunction with `@Table` (for a unique constraint bound to a single column, refer to `@Column`).

```
@Table(name="tbl_sky",
        uniqueConstraints = {@UniqueConstraint(columnNames={"month", "day"})})
)
```

A unique constraint is applied to the tuple `month, day`. Note that the `columnNames` array refers to the logical column names.

The logical column name is defined by the Hibernate NamingStrategy implementation. The default EJB3 naming strategy use the physical column name as the logical column name. Note that this may be different than the property name (if the column name is explicit).

Versioning for optimistic locking

You can add optimistic locking capability to an entity bean using the `@Version` annotation:

```
@Entity()
public class Flight implements Serializable {
    ...
    @Version
    @Column(name="OPTLOCK")
    public Integer getVersion() { ... }
}
```

The version property will be mapped to the `OPTLOCK` column, and the entity manager will use it to detect conflicting updates (preventing lost updates you might otherwise see with the last-commit-wins strategy).

The version column can be a numeric (the recommended solution) or a timestamp as per the EJB3 spec. Hibernate support any kind of type provided that you define and implement the appropriate `UserVersionType`.

2.2.2. Mapping simple properties

Declaring basic property mappings

Every non static property of an entity bean is considered persistent, unless you annotate it as `@Transient`. Not having an annotation for your property is equivalent to the appropriate `@Basic` annotation. The `@Basic` annotation allows you to declare the fetching strategy for a property:

```
@Transient
String getLengthInMeter() { ... }
```



```
String getName() {... } // persistent property

@Basic
int getLength() { ... } // persistent property

@Basic(fetch = FetchType.LAZY)
String getDetailedComment() { ... } // persistent property

@Basic(temporalType = TemporalType.TIME)
java.util.Date getDepartureTime() { ... } // persistent property
```

The `lengthInMeter` property is mapped transient and will be ignored by the entity manager. The `name` and the `length` properties are mapped persistent and eagerly fetched (the default for simple properties). The `detailedComment` property value will be lazily fetched from the database once a lazy property of the entity is accessed for the first time. Usually you don't need to lazy simple properties (not to be confused with lazy association fetching).

Note

To enable property level lazy fetching, your classes have to be instrumented: bytecode is added to the original one to enable such feature, please refer to the Hibernate reference documentation. If your classes are not instrumented, property level lazy loading is silently ignored.

The recommended alternative is to use the projection capability of EJB-QL or Criteria queries.

EJB3 support property mapping of all basic types supported by Hibernate (all basic Java types , their respective wrappers and serializable classes). Hibernate Annotations support out of the box Enum type mapping either into a numerical column (saving the enum ordinal) or a string based column (saving the enum string representation): the persistence representation is chosen at runtime depending on the underlying column. If you let hibernate generate the schema, then the numeric representation is going to be used.

In core Java APIs, the temporal precision is not defined. When dealing with temporal data you might want to describe the expected precision in database. Temporal data can have `DATE`, `TIME`, or `TIMESTAMP` precision (ie the actual date, only the time, or both). Use the `@Basic` annotation to fine tune that.

`@Lob` indicates that the property should be persisted in a Blob or a Clob depending of `LobType`. `java.sql.Clob`, `Character[]`, `char[]` and `java.lang.String` can be persisted in a Clob. `java.sql.Blob`, `Byte[]`, `byte[]` and serializable type can be persisted in a Blob.

```
@Lob(type=LobType.CLOB)
public String getFullText() {
    return fullText;
}

@Lob(type = LobType.BLOB)
public byte[] getFullCode() {
    return fullCode;
}
```

Note

`@Serialized` has been dropped from the EJB3 public draft, you can still use `@Type(type="serializable")` as an equivalent

Declaring column attributes

The column(s) used for a property mapping can be defined using the `@Column` annotation. Use it to override default values (see the EJB3 specification for more information on the defaults). You can use this annotation at the property level for properties that are:

- not annotated at all
- annotated with `@Basic`
- annotated with `@Version`
- annotated with `@Lob`
- annotated with `@org.hibernate.annotations.CollectionOfElements` (for Hibernate only)

```
@Entity
public class Flight implements Serializable {
    ...
    @Column(updatable = false, name = "flight_name", nullable = false, length=50)
    public String getName() { ... }
```

The `name` property is mapped to the `flight_name` column, which is not nullable, has a length of 50 and is not updatable (making the property immutable).

This annotation can be applied to regular properties as well as `@Id` or `@Version` properties.

```
@Column(
    name="columnName"; (1)
    boolean unique() default false; (2)
    boolean nullable() default true; (3)
    boolean insertable() default true; (4)
    boolean updatable() default true; (5)
    String columnDefinition() default ""; (6)
    String secondaryTable() default ""; (7)
    int length() default 255; (8)
    int precision() default 0; // decimal precision (9)
    int scale() default 0; // decimal scale
```

- (1) `name` (optional): the column name (default to the property name)
- (2) `unique` (optional): set a unique constraint on this column or not (default false)
- (3) `nullable` (optional): set the column as nullable (default false).
- (4) `insertable` (optional): whether or not the column will be part of the insert statement (default true)
- (5) `updatable` (optional): whether or not the column will be part of the update statement (default true)
- (6) `columnDefinition` (optional): override the sql DDL fragment for this particular column (non portable)
- (7) `secondaryTable` (optional): define the targeted table (default primary table)
- (8) `length` (optional): column length (default 255)
- (8) `precision` (optional): column decimal precision (default 0)
- (10) `scale` (optional): column decimal scale if useful (default 0)

Embedded objects (aka components)

It is possible to declare an embedded component inside an entity and even override its column mapping. Component classes have to be annotated at the class level with the `@Embeddable` annotation. It is possible to override the column mapping of an embedded object for a particular entity using the `@Embedded` and `@AttributeOverride` annotation in the associated property:

```

@Entity(access = AccessType.FIELD)
public class Person implements Serializable {

    // Persistent component using defaults
    Address homeAddress;

    @Embedded
    @AttributeOverrides( {
        @AttributeOverride(name="iso2", column = @Column(name="bornIso2") ),
        @AttributeOverride(name="name", column = @Column(name="bornCountryName") )
    } )
    Country bornIn;
    ...
}

```

```

@Embeddable(access = AccessType.FIELD)
public class Address implements Serializable {
    String city;
    Country nationality; //no overriding here
}

```

```

@Embeddable
public class Country implements Serializable {
    private String iso2;
    private String name;

    public String getIso2() { return iso2; }
    public void setIso2(String iso2) { this.iso2 = iso2; }

    @Column(name="countryName")
    public String getName() { return name; }
    public void setName(String name) { this.name = name; }
    ...
}

```

The `Person` entity bean has two component properties, `homeAddress` and `bornIn`. Note that the `homeAddress` property has not been annotated. Hibernate will guess that it is a persistent component by looking for the `@Embeddable` annotation in the `Address` class. We also override the mapping of a column name (to `bornCountryName`) with the `@Embedded` and `@AttributeOverride` annotations for each mapped attribute of `Country`. As you can see, `Country` is also a nested component of `Address`, again using auto-detection by Hibernate and EJB3 defaults. Overriding columns of embedded objects of embedded objects is currently not supported in the EJB3 spec, however, Hibernate Annotations supports it through dotted expressions.

```

@Embedded
@AttributeOverrides( {
    @AttributeOverride(name="city", column = @Column(name="fld_city") ),
    @AttributeOverride(name="nationality.iso2", column = @Column(name="nat_Iso2") ),
    @AttributeOverride(name="nationality.name", column = @Column(name="nat_CountryName") )
    //nationality columns in homeAddress are overridden
} )
Address homeAddress;

```

Hibernate Annotations supports one more feature that is not explicitly supported by the EJB3 public draft. You can annotate an embedded object with the `@EmbeddedSuperclass` annotation to make the superclass properties persistent (see `@EmbeddedSuperclass` for more information).

You cannot use association annotations in an embeddable object (ie no `.*ToOne` nor `.*ToMany`). This is disallowed by the spec, and not yet supported in Hibernate Annotations.

If you want to have the same embeddeable object type twice in the same entity, the column name defaulting will not work: at least one of the columns will have to be explicit. Hibernate goes beyond the EJB3 spec and allows you to enhance the defaulting mechanism through the `NamingStrategy`. `DefaultComponentSafeNamingStrategy` is a small improvement of the default `EJB3NamingStrategy` that allows embedded objects to be defaulted even if used twice in the same entity.

Non-annotated property defaults

If a property is not annotated, the following rules apply:

- If the property is of a single type, it is mapped as `@Basic`
- Otherwise, if the type of the property is annotated as `@Embeddable`
- Otherwise, if the type of the property is `Serializable`, it is mapped as `@Basic` in a column holding the object in its serialized version
- Otherwise, if the type of the property is `java.sql.Clob` or `java.sql.Blob`, it is mapped as `@Lob` with the appropriate `LobType`

2.2.. Mapping identifier properties

The `@Id` annotation lets you define which property is the identifier of your entity bean. It also allows you to define the identifier generation strategy:

- `AUTO` - either identity column or sequence depending the underlying DB
- `TABLE` - table holding the id
- `IDENTITY` - identity column
- `SEQUENCE` - sequence
- `NONE` - the application has the responsibility to set the id

Hibernate provides more id generators than the basic EJB3 ones. Check [Hibernate Annotation Extensions](#) for more informations.

The following example shows a sequence generator using the `SEQ_STORE` configuration (see below)

```
@Id(generate=GeneratorType.SEQUENCE, generator="SEQ_STORE" )
public Integer getId() { ... }
```

The next example uses the identity generator:

```
@Id(generate=GeneratorType.IDENTITY)
public Long getId() { ... }
```

The `AUTO` generator is the preferred type for portable applications (across several DB vendors). The identifier generation configuration can be shared for several `@Id` mappings with the `generator` attribute. There are several

configurations available through `@SequenceGenerator`, `@TableGenerator` and `@GeneratorTable`. The scope of a generator can be the application or the class. Class-defined generators are not visible outside the class and can override application level generators. Application level generators are defined at package level (see `package-info.java`):

```
@javax.persistence.GeneratedIdTable(
    name="GEN_TABLE",
    table = @Table(name="GENERATOR_TABLE"),
    pkColumnName = "key",
    valueColumnName = "hi"
)
@javax.persistence.TableGenerator(
    name="EMP_GEN",
    tableName="GEN_TABLE",
    pkColumnValue="EMP",
    allocationSize=20
)
@javax.persistence.SequenceGenerator(
    name="SEQ_GEN",
    sequenceName="my_sequence"
)
package org.hibernate.test.metadata;
```

If `package-info.java` in the `org.hibernate.test.metadata` package is used to initialize the EJB configuration, `EMP_GEN` and `SEQ_GEN` are application level generators. `EMP_GEN` defines a table based id generator using the hilo algorithm with a `max_lo` of 20 and keeping the `hi` value in a row of a table defined by the `GEN_TABLE` `@GeneratorTable`. The row has `EMP` as a primary key value. The table (described by the `@GeneratorTable`) is `GENERATOR_TABLE`, had the column `key` (which hold the primary key) and the column `hi` (which hold the next high value used).

`SEQ_GEN` defines a sequence generator using a sequence named `my_sequence`. Note that this version of Hibernate Annotations does not handle `initialValue` and `allocationSize` parameters in the sequence generator.

The next example shows the definition of a sequence generator in a class scope:

```
@Entity
@javax.persistence.SequenceGenerator(
    name="SEQ_STORE",
    sequenceName="my_sequence"
)
public class Store implements Serializable {
    private Long id;

    @Id(generator=GeneratorType.SEQUENCE, generator="SEQ_STORE")
    public Long getId() { return id; }
}
```

This class will use a sequence named `my_sequence` and the `SEQ_STORE` generator is not visible in other classes. Note that you can check the Hibernate Annotations tests in the `org.hibernate.test.metadata.id` package for more examples.

You can define a composite primary key through several syntaxes:

- annotate the component property as `@Id` and make the component class `@Embeddable`
- annotate the component property as `@EmbeddedId`
- annotate the class as `@IdClass`

While quite common to the EJB2 developer, `@IdClass` is likely new for Hibernate users. The composite primary key class corresponds to multiple fields or properties of the entity class, and the names of primary key fields or properties in the primary key class and those of the entity class must match and their types must be the same. Let's look at an example:

```
@Entity
@IdClass(FootballerPk.class)
public class Footballer {
    //part of the id key
    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    //part of the id key
    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }

    public String getClub() {
        return club;
    }

    public void setClub(String club) {
        this.club = club;
    }

    //appropriate equals() and hashCode() implementation
}

public class FootballerPk implements Serializable {
    //same name and type as in Footballer
    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    //same name and type as in Footballer
    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }

    //appropriate equals() and hashCode() implementation
}
```

As you may have seen, `@IdClass` points to the corresponding primary key class.

2.2.4. Mapping inheritance

EJB3 supports the three types of inheritance:

- Table per Class Strategy: the <union-class> element in Hibernate
- Single Table per Class Hierarchy Strategy: the <subclass> element in Hibernate
- Joined Subclass Strategy: the <joined-subclass> element in Hibernate

The chosen strategy is declared at the class level of the top level entity in the hierarchy using the `@Inheritance` annotation.

Note

Annotations of the interfaces is currently not supported.

Table per class

This strategy has many drawbacks (esp. with polymorphic queries and associations) explained in the EJB3 spec, the Hibernate reference documentation, Hibernate in Action, and many other places. Hibernate work around most of them implementing this strategy using `SQL UNION` queries. It is commonly used for the top level of an inheritance hierarchy:

```
@Entity
@Inheritance(strategy = InheritanceType.TABLE_PER_CLASS)
public class Flight implements Serializable {
```

This strategy support one to many associations provided that they are bidirectional. This strategy does not support the `IDENTITY` generator strategy: the id has to be shared across several tables. Consequently, when using this strategy, you should not use `AUTO`.

Single table per class hierarchy

All properties of all super- and subclasses are mapped into the same table, instances are distinguished by a special discriminator column:

```
@Entity
@Inheritance(
    strategy=InheritanceType.SINGLE_TABLE,
    discriminatorType=DiscriminatorType.STRING,
    discriminatorValue="Plane"
)
@DiscriminatorColumn(name="planetype")
public class Plane { ... }

@Entity
@Inheritance(
    discriminatorValue="A320"
)
public class A320 extends Plane { ... }
```

`Plane` is the superclass, it defines the inheritance strategy `InheritanceType.SINGLE_TABLE`, the discriminator type `DiscriminatorType.STRING`, and the discriminator value used for planes, `Plane`. It also defines the discriminator column through the `@DiscriminatorColumn(name="planetype")`. All of these attributes have sensible default values. The default name of the discriminator column is `TYPE`, and (for Hibernate) the default discriminator value is the fully qualified class name. `A320` is a subclass; you only have to define discriminator value if you don't want to use the default value. The strategy and the discriminator type is implicit.

Joined subclasses

The `@PrimaryKeyJoinColumn` and `@PrimaryKeyJoinColumns` annotations define the primary key(s) of the joined subclass table:

```
@Entity
@Inheritance(strategy=InheritanceType.JOINED )
public class Boat implements Serializable { ... }

@Entity
public class Ferry extends Boat { ... }

@Entity(access=AccessType.FIELD)
@PrimaryKeyJoinColumn(name="BOAT_ID")
public class AmericaCupClass extends Boat { ... }
```

Every entity bean declares the `JOINED` strategy, the `Ferry` table is joined with the `Boat` table using the same primary key names. The `AmericaCupClass` table is joined with `Boat` using the join condition `Boat.id = AmericaCupClass.BOAT_ID`.

Inherit properties from superclasses

This is sometimes useful to share common properties through a technical or a business superclass without including it as a regular mapped entity (ie no specific table for this entity). For that purpose you can map them as `@EmbeddableSuperclass`.

```
@EmbeddableSuperclass
public class BaseEntity {
    @Basic(temporalType = TemporalType.TIMESTAMP)
    public Date getLastUpdate() { ... }
    public String getLastUpdater() { ... }
    ...
}

@Entity class Order extends BaseEntity {
    @Id public Integer getId() { ... }
    ...
}
```

In database, this hierarchy will be represented as an `Order` table having the `id`, `lastUpdate` and `lastUpdater` columns. The embedded superclass property mappings are copied into their entity subclasses.. All sub entities will then use this strategy. Remember that the embeddable superclass is not the root of the hierarchy though.

Note

Properties from superclasses not mapped as `@EmbeddableSuperclass` are ignored.

Note

The same notion can be applied to `@Embeddable` objects to persist properties from their superclasses. You also need to use `@EmbeddableSuperclass` to do that (this should not be considered as a standard EJB3 feature though)

Note

It is not yet allowed to mark a class as `@EmbeddedSuperclass` in the middle of the mapped inheritance

hierarchy.

You can override columns defined in entity superclasses at the root entity level using the `@AttributeOverride` annotation.

```
@EmbeddableSuperclass
public class FlyingObject implements Serializable {

    public int getAltitude() {
        return altitude;
    }

    @Transient
    public int getMetricAltitude() {
        return metricAltitude;
    }
    ...
}

@Entity
@AttributeOverride( name="altitude", column = @Column(name="fld_altitude") )
public class Plane extends FlyingObject {
    ...
}
```

The altitude property will be persisted in an `fld_altitude` column of table `Plane`.

2.2.5. Mapping entity bean associations/relationships

One-to-one

You can associate entity beans through a one-to-one relationship using `@OneToOne`. There are two cases for one-to-one associations: either the associated entities share the same primary keys values or a foreign key is held by one of the entities (note that this FK column in the database should be constrained unique to simulate one-to-one multiplicity).

First, we map a real one-to-one association using shared primary keys:

```
@Entity
public class Body {
    @Id
    public Long getId() { return id; }

    @OneToOne(cascade = CascadeType.ALL)
    @PrimaryKeyJoinColumn
    public Heart getHeart() {
        return heart;
    }
    ...
}
```

```
@Entity
public class Heart {
    @Id(generate = GenerationType.NONE)
    public Long getId() { ...}
}
```

The one to one is marked as true by using the `@PrimaryKeyJoinColumn` annotation.

In the following example, the associated entities are linked through a foreign key column:

```
@Entity
public class Customer implements Serializable {
    @OneToOne(cascade = CascadeType.ALL)
    @JoinColumn(name="passport_fk")
    public Passport getPassport() {
        ...
    }
}

@Entity
public class Passport implements Serializable {
    @OneToOne(mappedBy = "passport")
    public Customer getOwner() {
        ...
    }
}
```

A `Customer` is linked to a `Passport`, with a foreign key column named `passport_fk` in the `Customer` table. The join column is declared with the `@JoinColumn` annotation which looks like the `@Column` annotation. It has one more parameter named `referencedColumnName`. This parameter declares the column in the targeted entity that will be used to the join. Note that when using `referencedColumnName` to a non primary key column, the associated class has to be `Serializable`. Also note that the `referencedColumnName` to a non primary key column has to be mapped to a property having a single column (other cases might not work).

The association may be bidirectional. In a bidirectional relationship, one of the sides (and only one) has to be the owner: the owner is responsible for the association column(s) update. To declare a side as *not* responsible for the relationship, the attribute `mappedBy` is used. `mappedBy` refers to the property name of the association on the owner side. In our case, this is `passport`. As you can see, you don't have to (must not) declare the join column since it has already been declared on the owners side.

If no `@JoinColumn` is declared on the owner side, the defaults apply. A join column(s) will be created in the owner table and its name will be the concatenation of the name of the relationship in the owner side, `_` (underscore), and the name of the primary key column(s) in the owned side. In this example `passport_id` because the property name is `passport` and the column `id` of `Passport` is `id`.

Many-to-one

Many-to-one associations are declared at the property level with the annotation `@ManyToOne`:

```
@Entity()
public class Flight implements Serializable {
    @ManyToOne( cascade = {CascadeType.CREATE, CascadeType.MERGE} )
    @JoinColumn(name="COMP_ID")
    public Company getCompany() {
        return company;
    }
    ...
}
```

The `@JoinColumn` attribute is optional, the default value(s) is like in one to one, the concatenation of the name of the relationship in the owner side, `_` (underscore), and the name of the primary key column in the owned side. In this example `company_id` because the property name is `company` and the column `id` of `Company` is `id`.

`@ManyToOne` has a parameter named `targetEntity` which describes the target entity name. You usually don't need this parameter since the default value (the type of the property that stores the association) is good in al-

most all cases. However this is useful when you want to use interfaces as the return type instead of the regular entity.

```

@Entity()
public class Flight implements Serializable {
    @ManyToOne( cascade = {CascadeType.CREATE, CascadeType.MERGE}, targetEntity=CompanyImpl.class )
    @JoinColumn(name="COMP_ID")
    public Company getCompany() {
        return company;
    }
    ...
}

public interface Company {
    ...
}

```

Collections

Overview

You can map `Collection`, `List` (ie ordered lists, not indexed lists), `Map` and `Set`. The EJB3 specification describes how to map an ordered list (ie a list ordered at load time) using `@javax.persistence.OrderBy` annotation: this annotation takes into parameter a list of comma separated (target entity) properties to order the collection by (eg `firstname asc, age desc`), if the string is empty, the collection will be ordered by id. `@OrderBy` currently works only on collections having no association table. For true indexed collections, please refer to the Hibernate Annotation Extensions. EJB3 allows you to map Maps using as a key one of the target entity property using `@MapKey(name="myProperty")` (`myProperty` is a property name in the target entity). When using `@MapKey` (without property name), the target entity primary key is used. Be aware that once loaded, the key is no longer kept in sync with the property, in other words, if you change the property value, the key will not change automatically in your Java model (Map support the way Hibernate 3 does is currently not supported in this release).

Hibernate has several notions of collections.

Table 2.1. Collections semantics

Semantic	java representation	annotations
Bag semantic	<code>java.util.List</code> , <code>java.util.Collection</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> , <code>@OneToMany</code> , <code>@ManyToMany</code>
List semantic	<code>java.util.List</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> , <code>@OneToMany</code> , <code>@ManyToMany</code> + <code>@OrderBy</code> , <code>@org.hibernate.annotations.IndexColumn</code>
Set semantic	<code>java.util.Set</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> , <code>@OneToMany</code> , <code>@ManyToMany</code>
Map semantic	<code>java.util.Map</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> , <code>@OneToMany</code> , <code>@ManyToMany</code> + <code>@MapKey</code>

So specifically, *java.util.List* collections with `@OrderBy` nor `@org.hibernate.annotations.IndexColumn` are going to be considered as bags.

Collection of primitive, core type or embedded objects is not supported by the EJB3 specification. Hibernate Annotations allows them however (see Hibernate Annotation Extensions).

```

@Entity public class City {
    @OneToMany(mappedBy="city")
    @OrderBy("streetName")
    public List<Street> getStreets() {
        return streets;
    }
    ...
}

@Entity public class Street {
    public String getStreetName() {
        return streetName;
    }

    @ManyToOne
    public City getCity() {
        return city;
    }
    ...
}

@Entity
public class Software {
    @OneToMany(mappedBy="software")
    @MapKey(name="codeName")
    public Map<String, Version> getVersions() {
        return versions;
    }
    ...
}

@Entity
@Table(name="tbl_version")
public class Version {
    public String getCodeName() {...}

    @ManyToOne
    public Software getSoftware() { ... }
    ...
}

```

So `City` has a collection of `Streets` that are ordered by `streetName` (of `Street`) when the collection is loaded. `Software` has a map of `Versions` which key is the `Version` `codeName`.

Unless the collection is a generic, you will have to define `targetEntity`. This is an annotation attribute that takes the target entity class as a value.

One-to-many

One-to-many associations are declared at the property level with the annotation `@OneToMany`. One to many associations may be bidirectional.

Bidirectional

Since many to one are (almost) always the owner side of a bidirectional relationship in the EJB3 spec, the one to many association is annotated by `@OneToMany(mappedBy=...)`

```
@Entity
```

```

public class Troop {
    @OneToMany(mappedBy="troop")
    public Set<Soldier> getSoldiers() {
        ...
    }

    @Entity
    public class Soldier {
        @ManyToOne
        @JoinColumn(name="troop_fk")
        public Troop getTroop() {
            ...
        }
    }
}

```

Troop has a bidirectional one to many relationship with Soldier through the `troop` property. You don't have to (must not) define any physical mapping in the `mappedBy` side.

To map a bidirectional one to many, with the one-to-many side as the owning side, you have to remove the `mappedBy` element and set the many to one `@JoinColumn` as insertable and updatable to false. This solution is obviously not optimized from the number of needed statements.

```

@Entity
public class Troop {
    @OneToMany
    @JoinColumn(name="troop_fk") //we need to duplicate the physical information
    public Set<Soldier> getSoldiers() {
        ...
    }
}

@Entity
public class Soldier {
    @ManyToOne
    @JoinColumn(name="troop_fk", insertable=false, updatable=false)
    public Troop getTroop() {
        ...
    }
}

```

Unidirectional

A unidirectional one to many using a foreign key column in the owned entity is not that common and not really recommended. We strongly advise you to use a join table for this kind of association (as explained in the next section). This kind of association is described through a `@JoinColumn`

```

@Entity
public class Customer implements Serializable {
    @OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
    @JoinColumn(name="CUST_ID")
    public Set<Ticket> getTickets() {
        ...
    }
}

@Entity
public class Ticket implements Serializable {
    ... //no bidir
}

```

Customer describes a unidirectional relationship with Ticket using the join column `CUST_ID`.

Unidirectional with join table

A unidirectional one to many with join table is much preferred. This association is described through an

@JoinTable.

```

@Entity()
public class Trainer {
    @OneToMany
    @JoinTable(
        table=@Table(name="TrainedMonkeys"),
        joinColumns = { @JoinColumn( name="trainer_id" ) },
        inverseJoinColumns = @JoinColumn( name="monkey_id" )
    )

    public Set<Monkey> getTrainedMonkeys() {
        ...
    }

    @Entity
    public class Monkey {
        ... //no bidir
    }
}

```

`Trainer` describes a unidirectional relationship with `Monkey` using the join table `TrainedMonkeys`, with a foreign key `trainer_id` to `Trainer` (`joinColumns`) and a foreign key `monkey_id` to `Monkey` (`inverseJoinColumns`).

Defaults

Without describing any physical mapping, a unidirectional one to many with join table is used. The table name is the concatenation of the owner table name, `_`, and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the owner table, `_`, and the owner primary key column(s) name. The foreign key name(s) referencing the other side is the concatenation of the owner property name, `_`, and the other side primary key column(s) name. A unique constraint is added to the foreign key referencing the other side table to reflect the one to many.

```

@Entity()
public class Trainer {
    @OneToMany
    public Set<Tiger> getTrainedTigers() {
        ...
    }

    @Entity
    public class Tiger {
        ... //no bidir
    }
}

```

`Trainer` describes a unidirectional relationship with `Tiger` using the join table `Trainer_Tiger`, with a foreign key `trainer_id` to `Trainer` (table name, `_`, `trainer id`) and a foreign key `trainedTigers_id` to `Monkey` (property name, `_`, `Tiger primary column`).

Many-to-many

Definition

A many-to-many association is defined logically using the `@ManyToMany` annotation. You also have to describe the association table and the join conditions using the `@JoinTable` annotation. If the association is bidirectional, one side has to be the owner and one side has to be the inverse end (ie. it will be ignored when updating the relationship values in the association table):

```

@Entity
public class Employer implements Serializable {
    @ManyToMany(
        targetEntity=org.hibernate.test.metadata.manytomany.Employee.class,
        cascade={CascadeType.CREATE, CascadeType.MERGE}
    )
    @JoinTable(
        table=@Table(name="EMPLOYER_EMPLOYEE"),
        joinColumns=@JoinColumn(name="EMPER_ID"),
        inverseJoinColumns=@JoinColumn(name="EMPEE_ID")
    )
    public Collection getEmployees() {
        return employees;
    }
    ...
}

```

```

@Entity
public class Employee implements Serializable {
    @ManyToMany(
        cascade={CascadeType.CREATE, CascadeType.MERGE},
        mappedBy="employees"
        targetEntity=Employer.class
    )
    public Collection getEmployers() {
        return employers;
    }
}

```

We've already shown the many declarations and the detailed attributes for associations. We'll go deeper in the `@JoinTable` description, it defines a `@Table`, an array of join columns (an array in annotation is defined using { A, B, C }), and an array of inverse join columns. The latter ones are the columns of the association table which refer to the `Employee` primary key (the "other side").

As seen previously, the other side don't have to (must not) describe the physical mapping: a simple `mappedBy` argument containing the owner side property name bind the two.

Default values

As any other annotations, most values are guessed in a many to many relationship. Without describing any physical mapping in a unidirectional many to many the following rules applied. The table name is the concatenation of the owner table name, `_` and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the owner table name, `_` and the owner primary key column(s). The foreign key name(s) referencing the other side is the concatenation of the owner property name, `_`, and the other side primary key column(s). These are the same rules used for a unidirectional one to many relationship.

```

@Entity()
public class Store {
    @ManyToMany(cascade = CascadeType.PERSIST)
    public Set<City> getImplantedIn() {
        ...
    }
}

@Entity()
public class City {
    ... //no bidirectional relationship
}

```

A `Store_Table` is used as the join table. The `store_id` column is a foreign key to the `Store` table. The `im-
plantedIn_id` column is a foreign key to the `City` table.

Without describing any physical mapping in a bidirectional many to many the following rules applied. The table name is the concatenation of the owner table name, `_` and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the other side property name, `_`, and the owner primary key column(s). The foreign key name(s) referencing the other side is the concatenation of the owner property name, `_`, and the other side primary key column(s). These are the same rules used for a unidirectional one to many relationship.

```
@Entity()
public class Store {
    @ManyToMany(cascade = {CascadeType.PERSIST, CascadeType.MERGE})
    public Set<Customer> getCustomers() {
        ...
    }
}

@Entity()
public class Customer {
    @ManyToMany(mappedBy="customers")
    public Set<Store> getStores() {
        ...
    }
}
```

A `Store_Customer` is used as the join table. The `stores_id` column is a foreign key to the `Store` table. The `customers_id` column is a foreign key to the `City` table.

Transitive persistence with cascading

You probably have noticed the `cascade` attribute taking an array of `CascadeType` as a value. The cascade concept in EJB3 is very similar to the transitive persistence and cascading of operations in Hibernate, but with slightly different semantics and cascading types:

- `CascadeType.PERSIST`: cascades the persist (create) operation to associated entities if `persist()` is called or if the entity is managed
- `CascadeType.MERGE`: cascades the merge operation to associated entities if `merge()` is called or if the entity is managed
- `CascadeType.REMOVE`: cascades the remove operation to associated entities if `delete()` is called
- `CascadeType.REFRESH`: cascades the refresh operation to associated entities if `refresh()` is called
- `CascadeType.ALL`: all of the above

Please refer to the chapter 6.3 of the EJB3 specification for more information on cascading and create/merge semantics.

Association fetching

You have the ability to either eagerly or lazily fetch associated entities. The `fetch` parameter can be set to `FetchType.LAZY` or `FetchType.EAGER`. `EAGER` will try to use an outer join select to retrieve the associated object, while `LAZY` is the default and will only trigger a select when the associated object is accessed for the first

time. EJBQL also has a `fetch` keyword that allows you to override laziness when doing a particular query. This is very useful to improve performance and is decided on a use case to use case basis.

2.2.6. Mapping composite primary and foreign keys

Composite primary keys use an embedded class as the primary key representation, so you'd use the `@Id` and `@Embeddable` annotations. Alternatively, you can use the `@EmbeddedId` annotation. Note that the dependent class has to be serializable and implements `equals()/hashCode()`. You can also use `@IdClass` as described in Mapping identifier properties.

```
@Entity
public class RegionalArticle implements Serializable {

    @Id
    public RegionalArticlePk getPk() { ... }
}

@Embeddable(access = AccessType.FIELD)
public class RegionalArticlePk implements Serializable { ... }
```

or alternatively

```
@Entity
public class RegionalArticle implements Serializable {

    @EmbeddedId
    public RegionalArticlePk getPk() { ... }
}

public class RegionalArticlePk implements Serializable { ... }
```

`@Embeddable` can define either a field or a property access strategy for the component. Composite foreign keys (if not using the default sensitive values) are defined on associations using the `@JoinColumn` element, which is basically an array of `@JoinColumn`. It is considered a good practice to express `referencedColumnName` explicitly. Otherwise, Hibernate will suppose that you use the same order of columns as in the primary key declaration.

```
@Entity(access = AccessType.FIELD)
public class Parent implements Serializable {
    @Id
    public ParentPk id;
    public int age;

    @OneToMany(cascade=CascadeType.ALL)
    @JoinColumns ({
        @JoinColumn(name="parentCivility", referencedColumnName = "isMale"),
        @JoinColumn(name="parentLastName", referencedColumnName = "lastName"),
        @JoinColumn(name="parentFirstName", referencedColumnName = "firstName")
    })
    public Set<Child> children; //unidirectional
    ...
}
```

```
@Entity(access = AccessType.FIELD)
public class Child implements Serializable {
    @Id(generate = GeneratorType.AUTO)
```

```

public Integer id;

@ManyToOne
@JoinColumns ({
    @JoinColumn(name="parentCivility", referencedColumnName = "isMale"),
    @JoinColumn(name="parentLastName", referencedColumnName = "lastName"),
    @JoinColumn(name="parentFirstName", referencedColumnName = "firstName")
})
public Parent parent; //unidirectional
}

```

```

@Embeddable(access = AccessType.FIELD)
public class ParentPk implements Serializable {
    String firstName;
    String lastName;
    ...
}

```

Note the explicit usage of the `referencedColumnName`.

2.2.7. Mapping secondary tables

You can map a single entity bean to several tables using the `@SecondaryTable` or `@SecondaryTables` class level annotations. To express that a column is in a particular table, use the `secondaryTable` parameter of `@Column` or `@JoinColumn`.

```

@Entity
@Table(name="MainCat")
@SecondaryTables({
    @SecondaryTable(name="Cat1", join={@JoinColumn(name="cat_id", referencedColumnName="id")},
    @SecondaryTable(name="Cat2", uniqueConstraints={@UniqueConstraint(columnNames={"storyPart2"})})
})
public class Cat implements Serializable {

    private Integer id;
    private String name;
    private String storyPart1;
    private String storyPart2;

    @Id(generate = GeneratorType.AUTO)
    public Integer getId() {
        return id;
    }

    public String getName() {
        return name;
    }

    @Column(secondaryTable="Cat1")
    public String getStoryPart1() {
        return storyPart1;
    }

    @Column(secondaryTable="Cat2")
    public String getStoryPart2() {
        return storyPart2;
    }
}

```

In this example, `name` will be in `MainCat`, `storyPart1` will be in `Cat1` and `storyPart2` will be in `Cat2`. `Cat1` will be joined to `MainCat` using the `cat_id` as a foreign key, and `Cat2` using `id` (ie the same column name, the

mainCat id column has). Plus a unique constraint on storyPart2 has been set.

Check out the JBoss EJB 3 tutorial or the Hibernate Annotations unit test suite for more examples.

2.3. Mapping Queries

2.3.1. Mapping EJBQL/HQL queries

You can map EJBQL/HQL queries using annotations. `@NamedQuery` and `@NamedQueries` can be defined at the class or at the package level. However their definitions are global to the session factory/entity manager factory scope. A named query is defined by its name and the actual query string.

```

javax.persistence.NamedQueries(
    @javax.persistence.NamedQuery(name="plane.getAll", queryString="select p from Plane p")
)
package org.hibernate.test.annotations.query;

...

@Entity
@NamedQuery(name="night.moreRecentThan", queryString="select n from Night n where n.date >=:date")
public class Night {
    ...
}

public class MyDao {
    doStuff() {
        Query q = s.getNamedQuery("night.moreRecentThan");
        q.setDate( "date", aMonthAgo );
        List results = q.list();
        ...
    }
    ...
}

```

2.3.2. Mapping native queries

You can also map a native query (ie a plain SQL query). To achieve that, you need to describe the SQL result-set structure using `@SqlResultSetMapping`. Like `@NamedQuery`, a `@SqlResultSetMapping` can be defined at both package level or class level. However its scope is global to the application. As we will see, a `resultSetMapping` parameter is defined the `@NamedNativeQuery`, it represents the name of a defined `@SqlResultSetMapping`. The resultset mapping declares the entities retrieved by this native query. Each field of the entity is bound to an SQL alias (or column name). All fields of the entity including the ones of subclasses has to be present in the SQL query. Field definitions are optional provided that they map to the same column name as the one declared on the class property.

```

@NamedNativeQuery(name="night&area", queryString="select night.id nid, night.night_duration, "
    + " night.night_date, area.id aid, night.area_id, area.name "
    + "from Night night, Area area where night.area_id = area.id", resultSetMapping="joinMapping")
@SqlResultSetMapping(name="joinMapping", entities={
    @EntityResult(name="org.hibernate.test.annotations.query.Night", fields = {
        @FieldResult(name="id", column="nid"),
        @FieldResult(name="duration", column="night_duration"),
        @FieldResult(name="date", column="night_date"),
        @FieldResult(name="area", column="area_id"),
        discriminatorColumn="disc"
    }
}),

```

```

@EntityResult(name="org.hibernate.test.annotations.query.Area", fields = {
    @FieldResult(name="id", column="aid"),
    @FieldResult(name="name", column="name")
})
}
)

```

In the above example, the `night&area` named query use the `joinMapping` result set mapping. This mapping returns 2 entities, `Night` and `Area`, each property is declared and associated to a column name, actually the column name retrieved by the query. Let's now see an implicit declaration of the property / column.

```

@Entity
@SqlResultSetMapping(name="implicit", entities=@EntityResult(name="org.hibernate.test.annotations.query.SpaceShip", fields=@FieldResult(name="name", column="name"), @FieldResult(name="model", column="model_txt"), @FieldResult(name="speed", column="speed")))
@NamedNativeQuery(name="implicitSample", queryString="select * from SpaceShip", resultSetMapping="implicit")
public class SpaceShip {
    private String name;
    private String model;
    private double speed;

    @Id(generate = GeneratorType.NONE)
    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @Column(name="model_txt")
    public String getModel() {
        return model;
    }

    public void setModel(String model) {
        this.model = model;
    }

    public double getSpeed() {
        return speed;
    }

    public void setSpeed(double speed) {
        this.speed = speed;
    }
}

```

In this example, we only describe the entity member of the result set mapping. The property / column mappings is done using the entity mapping values. In this case the `model` property is bound to the `model_txt` column.

If you retrieve a single entity and if you use the default mapping, you can use the `resultClass` attribute instead of `resultSetMapping`:

```

@NamedNativeQuery(name="implicitSample", queryString="select * from SpaceShip",
    resultClass=SpaceShip.class)
public class SpaceShip {

```

2.4. Hibernate Annotation Extensions

Hibernate 3.1 offers a variety of additional annotations that you can mix/match with your EJB 3 entities. They have been designed as a natural extension of EJB3 annotations.

To empower the EJB3 capabilities, hibernate provides specific annotations that match hibernate features. The

`org.hibernate.annotations` package contains all these annotations extensions.

2.4.1. Entity

You can fine tune some of the actions done by Hibernate on entities beyond what the EJB3 spec offers.

`@org.hibernate.annotations.Entity` adds additional metadata that may be needed beyond what is defined in the standard `@Entity`

- `mutable`: whether this entity is mutable or not
- `dynamicInsert`: allow dynamic SQL for inserts
- `dynamicUpdate`: allow dynamic SQL for updates
- `selectBeforeUpdate`: Specifies that Hibernate should never perform an SQL UPDATE unless it is certain that an object is actually modified.
- `polymorphism`: whether the entity polymorphism is of `PolymorphismType.IMPLICIT` (default) or `PolymorphismType.EXPLICIT`
- `persister`: allow the overriding of the default persister implementation
- `optimisticLock`: optimistic locking strategy (`OptimisticLockType.VERSION`, `OptimisticLockType.NONE`, `OptimisticLockType.DIRTY` or `OptimisticLockType.ALL`)

Note

`@javax.persistence.Entity` is still mandatory, `@org.hibernate.annotations.Entity` is not a replacement.

Here are some additional Hibernate annotation extensions

`@org.hibernate.annotations.BatchSize` allows you to define the batch size when fetching instances of this entity (eg. `@BatchSize(size=4)`). When loading a given entity, Hibernate will then load all the uninitialized entities of the same type in the persistence context up to the batch size.

`@org.hibernate.annotations.Proxy` defines the laziness attributes of the entity. `lazy` (default to true) define whether the class is lazy or not. `proxyClassName` is the interface used to generate the proxy (default is the class itself).

`@org.hibernate.annotations.Where` defines an optional SQL WHERE clause used when instances of this class is retrieved.

`@org.hibernate.annotations.Check` defines an optional check constraints defined in the DDL statement.

`@OnDelete(action=OnDeleteAction.CASCADE)` on joined subclasses: use a SQL cascade delete on deletion instead of the regular Hibernate mechanism.

`@Table(name="tableName", indexes = { @Index(name="index1", columnNames={"column1", "column2"}) })` creates the defined indexes on the columns of table `tableName`. This can be applied on the primary table or any secondary table. The `@Tables` annotation allows your to apply indexes on different tables. This annotation is expected where `@javax.persistence.Table` OR `@javax.persistence.SecondaryTable(s)` occurs. `@org.hibernate.annotations.Table` is a complement, not a replacement to `@javax.persistence.Table`

```

@Entity
@BatchSize(size=5)
@org.hibernate.annotations.Entity(
    selectBeforeUpdate = true,
    dynamicInsert = true, dynamicUpdate = true,
    optimisticLock = OptimisticLockType.ALL,
    polymorphism = PolymorphismType.EXPLICIT)
@Where(clause="1=1")
@org.hibernate.annotations.Table(name="Forest", indexes = { @Index(name="idx", columnNames = { "name"
public class Forest { ... }

```

```

@Entity
@Inheritance(
    strategy=InheritanceType.JOINED
)
public class Vegetable { ... }

@Entity
@onDelete(action=onDeleteAction.CASCADE)
public class Carrot extends Vegetable { ... }

```

2.4.2. Identifier

`@org.hibernate.annotations.GenericGenerator` allows you to define an Hibernate specific id generator.

```

@Id(generator="system-uuid")
@GenericGenerator(name="system-uuid", strategy = "uuid")
public String getId() {

@Id(generator="hibseq")
@GenericGenerator(name="hibseq", strategy = "seqhilo",
    parameters = {
        @Parameter(name="max_lo", value = "5"),
        @Parameter(name="sequence", value="heybabyhey")
    }
)
public Integer getId() {

```

`strategy` is the short name of an Hibernate3 generator strategy or the fully qualified class name of an `IdentifierGenerator` implementation. You can add some parameters through the `parameters` attribute

2.4.3. Property

Formula

Sometimes, you want the Database to do some computation for you rather than in the JVM, you might also create some kind of virtual column. You can use a SQL fragment (aka formula) instead of mapping a property into a column. This kind of property is read only (its value is calculated by your formula fragment).

```

@Formula("obj_length * obj_height * obj_width")
public long getObjectVolume()

```

The SQL fragment can be as complex as you want avec even include subselects.

Type

`@org.hibernate.annotations.Type` overrides the default hibernate type used: this is generally not necessary

since the type is correctly inferred by Hibernate. Please refer to the Hibernate reference guide for more information on the Hibernate types.

`@org.hibernate.annotations.TypeDef` and `@org.hibernate.annotations.TypeDefs` allows you to declare type definitions. These annotations are placed at the class or package level. Note that these definitions will be global for the session factory (even at the class level) and that type definition has to be defined before any usage.

```
@TypeDefs(
{
  @TypeDef(
    name="caster",
    typeClass = CasterStringType.class,
    parameters = {
      @Parameter(name="cast", value="lower")
    }
  )
}
)
package org.hibernate.test.annotations.entity;

...
public class Forest {
  @Type(type="caster")
  public String getSmallText() {
    ...
  }
}
```

When using composite user type, you will have to express column definitions. The `@Columns` has been introduced for that purpose.

```
@Type(type="org.hibernate.test.annotations.entity.MonetaryAmountUserType")
@Columns(columns = {
  @Column(name="r_amount"),
  @Column(name="r_currency")
})
public MonetaryAmount getAmount() {
  return amount;
}

public class MonetaryAmount implements Serializable {
  private BigDecimal amount;
  private Currency currency;
  ...
}
```

Index

You can define an index on a particular column using the `@Index` annotation on a one column property, the `columnNames` attribute will then be ignored

```
@Column(secondaryTable="Cat1")
@Index(name="story1index")
public String getStoryPart1() {
  return storyPart1;
}
```

2.4.4. Inheritance

`SINGLE_TABLE` is a very powerful strategy but sometimes, and especially for legacy systems, you cannot add

an additional discriminator column. For that purpose Hibernate has introduced the notion of discriminator formula: `@DiscriminatorFormula` is a replacement of `@DiscriminatorColumn` and use a SQL fragment as a formula for discriminator resolution (no need to have a dedicated column).

```
@Entity
@DiscriminatorFormula("case when forest_type is null then 0 else forest_type end")
public class Forest { ... }
```

2.4.5. Association related annotations

By default, when Hibernate cannot resolve the association because the expected associated element is not in database (wrong id on the association column), an exception is raised by Hibernate. This might be inconvenient for legacy and badly maintained schemas. You can ask Hibernate to ignore such elements instead of raising an exception using the `@NotFound` annotation. This annotation can be used on a `@OneToOne` (with FK), `@ManyToOne`, `@OneToMany` OR `@ManyToMany` association.

```
@Entity
public class Child {
    ...
    @ManyToOne
    @NotFound(action=NotFoundAction.IGNORE)
    public Parent getParent() { ... }
    ...
}
```

2.4.6. Collection related annotations

Parameter annotations

It is possible to set

- the batch size for collections using `@BatchSize`
- the where clause, using `@Where`
- the check clause, using `@Check`
- the SQL order by clause, using `@OrderBy`
- the delete cascade strategy through `@OnDelete(action=OnDeleteAction.CASCADE)`

You can also declare a sort comparator. Use the `@Sort` annotation. Expressing the comparator type you want between unsorted, natural or custom comparator. If you want to use your own comparator implementation, you'll also have to express the implementation class using the `comparator` attribute.

```
@OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
@JoinColumn(name="CUST_ID")
@Sort(type = SortType.COMPARATOR, comparator = TicketComparator.class)
@Where(clause="1=1")
@OnDelete(action=OnDeleteAction.CASCADE)
public SortedSet<Ticket> getTickets() {
    return tickets;
}
```

Please refer to the previous descriptions of these annotations for more informations.

Extra collection types

Beyond EJB3, Hibernate Annotations supports true `List` and `Array`. Map your collection the same way as usual and add the `@IndexColumn`. This annotation allows you to describe the column that will hold the index. You can also declare the index value in DB that represent the first element (aka as base index). The usual value is 0 or 1.

```
@OneToMany(cascade = CascadeType.ALL)
@IndexColumn(name = "drawer_position", base=1)
public List<Drawer> getDrawers() {
    return drawers;
}
```

Note

If you forgot to set `@IndexColumn`, the bag semantic is applied

Hibernate Annotations also supports collections of core types (`Integer`, `String`, `Enums`, ...), collections of embeddable objects and even arrays of primitive types. This is known as collection of elements.

A collection of elements as to be annotated as `@CollectionOfElements` (as a replacement of `@OneToMany`) To define the collection table, the `@JoinTable` annotation is used on the association property, `joinColumns` defines the join columns between the entity primary table and the collection table (`inverseJoinColumn` is useless and should be left empty). For collection of core types or array of primitive types, you can override the element column definition using a `@Column` on the association property. You can also override the columns of a collection of embeddable object using `@AttributeOverride`.

```
@Entity
public class Boy {
    private Integer id;
    private Set<String> nickNames = new HashSet<String>();
    private int[] favoriteNumbers;
    private Set<Toy> favoriteToys = new HashSet<Toy>();
    private Set<Character> characters = new HashSet<Character>();

    @Id(generate= GeneratorType.AUTO)
    public Integer getId() {
        return id;
    }

    @CollectionOfElements
    public Set<String> getNickNames() {
        return nickNames;
    }

    @CollectionOfElements
    @JoinTable(
        table=@Table(name="BoyFavoriteNumbers"),
        joinColumns = @JoinColumn(name="BoyId")
    )
    @Column(name="favoriteNumber", nullable=false)
    @IndexColumn(name="nbr_index")
    public int[] getFavoriteNumbers() {
        return favoriteNumbers;
    }

    @CollectionOfElements
    @AttributeOverride( name="serial", column=@Column(name="serial_nbr") )
    public Set<Toy> getFavoriteToys() {
        return favoriteToys;
    }

    @CollectionOfElements
```

```

    public Set<Character> getCharacters() {
        return characters;
    }
    ...
}

public enum Character {
    GENTLE,
    NORMAL,
    AGGRESSIVE,
    ATTENTIVE,
    VIOLENT,
    CRAFTY
}

@Embeddable(access = AccessType.FIELD)
public class Toy {
    public String name;
    public String serial;

    public boolean equals(Object o) {
        if ( this == o ) return true;
        if ( o == null || getClass() != o.getClass() ) return false;

        final Toy toy = (Toy) o;

        if ( !name.equals( toy.name ) ) return false;
        if( !serial.equals( toy.serial ) ) return false;

        return true;
    }

    public int hashCode() {
        int result;
        result = name.hashCode();
        result = 29 * result + serial.hashCode();
        return result;
    }
}

```

Note

Previous versions of Hibernate Annotations used the `@OneToMany` to mark a collection of elements. Due to semantic inconsistencies, we've introduced the annotation `@CollectionOfElements`. Marking collections of elements the old way still work but is considered deprecated and is going to be unsupported in future releases

2.4.7. Cache

In order to optimize your database accesses, you can activate the so called second level cache of Hibernate. This cache is configurable on a per entity and per collection basis.

`@org.hibernate.annotations.Cache` defines the caching strategy and region of a given second level cache. This annotation can be applied on the root entity (not the sub entities), and on the collections.

```

@Entity
@Cache(usage = CacheConcurrencyStrategy.NONSTRICT_READ_WRITE)
public class Forest { ... }

```

```

@OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
@JoinColumn(name="CUST_ID")
@Cache(usage = CacheConcurrencyStrategy.NONSTRICT_READ_WRITE)
public SortedSet<Ticket> getTickets() {
    return tickets;
}

```

```
@Cache(
    CacheConcurrencyStrategy usage();           (1)
    String region() default "";                 (2)
    String include() default "all";            (3)
)
```

- (1) `usage`: the given cache concurrency strategy (`NONE`, `READ_ONLY`, `NONSTRICT_READ_WRITE`, `READ_WRITE`, `TRANSACTIONAL`)
- (2) `region` (optional): the cache region (default to the fqcn of the class or the fq role name of the collection)
- (3) `include` (optional): all to include all properties, non-lazy to only include non lazy properties (default all).

2.4.8. Filters

Hibernate has the notion of data filter that can be applied at runtime on a given session. Those filters has to be defined first.

`@org.hibernate.annotations.FilterDef` or `@FilterDefs` define filter definition(s) used by filter(s) using the same name. A filter definition has a `name()` and an array of `parameters()`. A `@ParamDef` has a name and a type. You can also define a `defaultCondition()` parameter for a given `@filterDef` to set the default condition to use when none are defined in the `@Filter`. A `@FilterDef(s)` can be defined at the class or package level.

We now need to define the SQL filter clause applied to either the entity load or the collection load. `@Filter` is used and placed either on the entity or the collection element

```
@Entity
@FilterDef(name="minLength", parameters={ @ParamDef( name="minLength", type="integer" ) } )
@Filters( {
    @Filter(name="betweenLength", condition=":minLength <= length and :maxLength >= length"),
    @Filter(name="minLength", condition=":minLength <= length")
} )
public class Forest { ... }
```

2.4.9. Queries

Since Hibernate has more features on named queries than the one defined in the EJB3 specification, `@org.hibernate.annotations.NamedQuery`, `@org.hibernate.annotations.NamedQueries`, `@org.hibernate.annotations.NamedNativeQuery` and `@org.hibernate.annotations.NamedNativeQueries` have been introduced. They add some attributes to the standard version and can be used as a replacement:

- `flushMode`: define the query flush mode (Always, Auto, Commit or Never)
- `cacheable`: whether the query should be cached or not
- `cacheRegion`: cache region used if the query is cached
- `fetchSize`: JDBC statement fetch size for this query
- `timeout`: query time out
- `callable`: for native queries only, to be set to true for stored procedures
- `comment`: if comments are activated, the comment seen when the query is sent to the database.
- `cacheMode`: Cache interaction mode (get, ignore, normal, put or refresh)

- `readOnly`: whether or not the elements retrieved from the query are in read only mode.

Chapter 3. Hibernate Validator

Annotations are a very convenient and elegant way to specify invariant constraints for a domain model. You can, for example, express that a property should never be null, that the account balance should be strictly positive, etc. These domain model constraints are declared in the bean itself by annotating its properties. A validator can then read them and check for constraint violations. The validation mechanism can be executed in different layers in your application without having to duplicate any of these rules (presentation layer, data access layer). Hibernate Validator has been designed for that purpose.

Hibernate Validator works at two levels. First, it is able to check in-memory instances of a class for constraint violations. Second, it can apply the constraints to the Hibernate metamodel and incorporate them into the generated database schema.

Each constraint annotation is associated to a validator implementation responsible for checking the constraint on the entity instance. A validator can also (optionally) apply the constraint to the Hibernate metamodel, allowing Hibernate to generate DDL that expresses the constraint. With the appropriate event listener, you can execute the checking operation on inserts and updates done by Hibernate. Hibernate Validator is not limited to use with Hibernate. You can easily use it anywhere in your application.

When checking instances at runtime, Hibernate Validator returns information about constraint violations in an array of `InvalidValues`. Among other information, the `InvalidValue` contains an error description message that can embed the parameter values bundle with the annotation (eg. length limit), and message strings that may be externalized to a `ResourceBundle`.

3.1. Constraints

3.1.1. What is a constraint?

A constraint is represented by an annotation. A constraint usually has some attributes used to parameterize the constraints limits. The constraint apply to the annotated element.

3.1.2. Built in constraints

Hibernate Validator comes with some built-in constraints, which covers most basic data checks. As we'll see later, you're not limited to them, you can in a minute write your own constraints.

Table 3.1. Built-in constraints

Annotation	Apply on	Runtime checking	Hibernate Metadata impact
<code>@Length(min=, max=)</code>	property (String)	check if the string length match the range	Column length will be set to max
<code>@Max(value=)</code>	property (numeric or string representation of a numeric)	check if the value is less than or equals to max	Add a check constraint on the column
<code>@Min(value=)</code>	property (numeric or string representation of a numeric)	check if the value is more than or equals to min	Add a check constraint on the column

Annotation	Apply on	Runtime checking	Hibernate Metadata impact
	numeric)		
@NotNull	property	check if the value is not null	Column(s) are not null
@Past	property (date or calendar)	check if the date is in the past	Add a check constraint on the column
@Future	property (date or calendar)	check if the date is in the future	none
@Pattern(regex="regexp", flag=)	property (string)	check if the property match the regular expression given a match flag (see <code>java.util.regex.Pattern</code>)	none
@Range(min=, max=)	property (numeric or string representation of a numeric)	check if the value is between min and max (included)	Add a check constraint on the column
@Size(min=, max=)	property (array, collection, map)	check if the element size is between min and max (included)	none
@AssertFalse	property	check that the method evaluates to false (useful for constraints expressed in code rather than annotations)	none
@AssertTrue	property	check that the method evaluates to true (useful for constraints expressed in code rather than annotations)	none
@Valid	property (object)	Perform validation recursively on the associated object	none

3.1.3. Error messages

Hibernate Validator comes with a default set of error messages translated in a few languages (if yours is not part of it, please send us a patch). You can override those messages by creating a `ValidatorMessages.properties` or `(ValidatorMessages_loc.properties)` out of `org.hibernate.validator.resources.DefaultValidatorMessages.properties` and change the appropriate keys. You can even add your own additional set of messages while writing your validator annotations.

Alternatively you can provide a `ResourceBundle` while checking programmatically the validation rules on a bean.

3.1.4. Writing your own constraints

Extending the set of built-in constraints is extremely easy. Any constraint consists of two pieces: the constraint *descriptor* (the annotation) and the constraint *validator* (the implementation class). Here is a simple user-defined descriptor:

```
@ValidatorClass(CapitalizedValidator.class)
@Target(METHOD)
@Retention(RUNTIME)
@Documented
public @interface Capitalized {
    CapitalizeType type default Capitalize.FIRST;
    String message() default "has incorrect capitalization";
}
```

`type` is a parameter describing how the property should to be capitalized. This is a user parameter fully dependant on the annotation business.

`message` is the default string used to describe the constraint violation and is mandatory. You can hard code the string or you can externalize part/all of it through the Java ResourceBundle mechanism. Parameters values are going to be injected inside the message when the `{parameter}` string is found (in our example `Capitalization` is not `{type}` would generate `Capitalization is not FIRST`), externalizing the whole string in `ValidatorMessages.properties` is considered good practice. See [Error messages](#).

```
@ValidatorClass(CapitalizedValidator.class)
@Target(METHOD)
@Retention(RUNTIME)
@Documented
public @interface Capitalized {
    CapitalizeType type default Capitalize.FIRST;
    String message() default "{validator.capitalized}";
}

...
#in ValidatorMessages.properties
validator.capitalized=capitalization is not {type}
```

As you can see the `{ }` notation is recursive.

To link a descriptor to its validator implementation, we use the `@ValidatorClass` meta-annotation. The validator class parameter must name a class which implements `Validator<ConstraintAnnotation>`.

We now have to implement the validator (ie. the rule checking implementation). A validation implementation can check the value of the a property (by implementing `PropertyConstraint`) and/or can modify the hibernate mapping metadata to express the constraint at the database level (by implementing `PersistentClassConstraint`).

```
public class LengthValidator
    implements Validator<Capitalized>, PropertyConstraint {
    private CapitalizeType type;

    //part of the Validator<Annotation> contract,
    //allows to get and use the annotation values
    public void initialize(Capitalized parameters) {
        type = parameters.type();
    }

    //part of the property constraint contract
    public boolean isValid(Object value) {
        if (value==null) return true;
        if ( !(value instanceof String) ) return false;
        String string = (String) value;
```

```

        if (type == CapitalizeType.ALL) {
            return string.equals( string.toUpperCase() );
        }
        else {
            String first = string.substring(0,1);
            return first.equals( first.toUpperCase());
        }
    }
}

```

The `isValid()` method should return false if the constraint has been violated. For more examples, refer to the built-in validator implementations.

We only have seen property level validation, but you can write a Bean level validation annotation. Instead of receiving the return instance of a property, the bean itself will be passed to the validator. To activate the validation checking, just annotated the bean itself instead. A small sample can be found in the unit test suite.

3.1.5. Annotating your domain model

Since you are already familiar with annotations now, the syntax should be very familiar.

```

public class Address {
    private String line1;
    private String line2;
    private String zip;
    private String state;
    private String country;
    private long id;

    // a not null string of 20 characters maximum
    @Length(max=20)
    @NotNull
    public String getCountry() {
        return country;
    }

    // a non null string
    @NotNull
    public String getLine1() {
        return line1;
    }

    //no constraint
    public String getLine2() {
        return line2;
    }

    // a not null string of 3 characters maximum
    @Length(max=3) @NotNull
    public String getState() {
        return state;
    }

    // a not null numeric string of 5 characters maximum
    // if the string is longer, the message will
    //be searched in the resource bundle at key 'long'
    @Length(max=5, message="{long}")
    @Pattern(regex="[0-9]+")
    @NotNull
    public String getZip() {
        return zip;
    }

    // should always be true
    @AssertTrue
    public boolean isValid() {

```



```

        return true;
    }

    // a numeric between 1 and 2000
    @Id @Min(1)
    @Range(max=2000)
    public long getId() {
        return id;
    }
}

```

While the example only shows public property validation, you can also annotate fields of any kind of visibility.

```

@MyBeanConstraint(max=45)
public class Dog {
    @AssertTrue private boolean isMale;
    @NotNull protected String getName() { ... };
    ...
}

```

You can also annotate interfaces. Hibernate Validator will check all superclasses and interfaces extended or implemented by a given bean to read the appropriate validator annotations.

```

public interface Named {
    @NotNull String getName();
    ...
}

public class Dog implements Named {

    @AssertTrue private boolean isMale;

    public String getName() { ... };

}

```

The name property will be checked for nullity when the Dog bean is validated.

3.2. Using the Validator framework

Hibernate Validator is intended to be used to implement multi-layered data validation, where we express constraints in one place (the annotated domain model) and apply them at various different layers of the application.

3.2.1. Database schema-level validation

Out of the box, Hibernate Annotations will translate the constraints you have defined for your entities into mapping metadata. For example, if a property of your entity is annotated `@NotNull`, its columns will be declared as `not null` in the DDL schema generated by Hibernate.

3.2.2. Hibernate event-based validation

Hibernate Validator has two built-in Hibernate event listeners. Whenever a `PreInsertEvent` or `PreUpdateEvent` occurs, the listeners will verify all constraints of the entity instance and throw an exception if any constraint is violated. Basically, objects will be checked before any inserts and before any updates made by Hibernate. This is the most convenient and the easiest way to activate the validation process. On constraint violation, the event will raise a runtime `InvalidStateException` which contains an array of `InvalidValues` describing each failure.

```

<hibernate-configuration>
  ...
  <event type="pre-update">
    <listener
      class="org.hibernate.validator.event.ValidatePreUpdateEventListener"/>
  </event>
  <event type="pre-insert">
    <listener
      class="org.hibernate.validator.event.ValidatePreInsertEventListener"/>
  </event>
</hibernate-configuration>
    
```

Note

When using Hibernate Entity Manager, the Validation framework is activated out of the box. If the beans are not annotated with validation annotations, there is no performance cost.

3.2.3. Application-level validation

Hibernate Validator can be applied anywhere in your application code.

```

ClassValidator personValidator = new ClassValidator( Person.class );
ClassValidator addressValidator = new ClassValidator( Address.class, ResourceBundle.getBundle("message") );

InvalidValue[] validationMessages = addressValidator.getInvalidValues(address);
    
```

The first two lines prepare the Hibernate Validator for class checking. The first one relies upon the error messages embedded in Hibernate Validator (see Error messages), the second one uses a resource bundle for these messages. It is considered a good practice to execute these lines once and cache the validator instances.

The third line actually validates the `Address` instance and returns an array of `InvalidValues`. Your application logic will then be able to react to the failure.

You can also check a particular property instead of the whole bean. This might be useful for property per property user interaction

```

ClassValidator addressValidator = new ClassValidator( Address.class, ResourceBundle.getBundle("message") );

//only get city property invalid values
InvalidValue[] validationMessages = addressValidator.getInvalidValues(address, "city");

//only get potential city property invalid values
InvalidValue[] validationMessages = addressValidator.getPotentialInvalidValues("city", "Paris")
    
```

3.2.4. Validation informations

As a validation information carrier, hibernate provide an array of `InvalidValue`. Each `InvalidValue` has a bunch of methods describing the individual issues.

`getBeanClass()` retrieves the failing bean type

`getBean()` retrieves the failing instance (if any ie not when using `getPotentialInvalidValues()`)

`getValue()` retrieves the failing value

`getMessage()` retrieves the proper internationalized error message

`getRootBean()` retrieves the root bean instance generating the issue (useful in conjunction with `@Valid`), is null if `getPotentialInvalidValues()` is used.

`getPropertyPath()` retrieves the dotted path of the failing property starting from the root bean

Chapter 4. Hibernate Lucene Integration

Lucene is a high-performance Java search engine library available from the Apache Software Foundation. Hibernate Annotations includes a package of annotations that allows you to mark any domain model object as indexable and have Hibernate maintain a Lucene index of any instances persisted via Hibernate.

4.1. Using Lucene to index your entities

4.1.1. Annotating your domain model

First, we must declare a persistent class as `@Indexed`:

```
@Entity
@Indexed(index="indexes/essays")
public class Essay {
    ...
}
```

The `index` attribute tells Hibernate where the Lucene index is located (a directory on your file system). If you wish to define a base directory for all lucene indexes, you can use the `hibernate.lucene.index_dir` property in your configuration file.

Lucene indexes contain four kinds of fields: *keyword* fields, *text* fields, *unstored* fields and *unindexed* fields. Hibernate Annotations provides annotations to mark a property of an entity as one of the first three kinds of indexed fields.

```
@Entity
@Indexed(index="indexes/essays")
public class Essay {
    ...

    @Id
    @Keyword(id=true)
    public Long getId() { return id; }

    @Text(name="Abstract")
    public String getSummary() { return summary; }

    @Lob
    @Unstored
    public String getText() { return text; }
}
```

These annotations define an index with three fields: `Id`, `Abstract` and `Text`.

Note: you *must* specify `@Keyword(id=true)` on the identifier property of your entity class.

The analyzer class used to index the elements is configurable through the `hibernate.lucene.analyzer` property. If none defined, `org.apache.lucene.analysis.standard.StandardAnalyzer` is used as the default.

4.1.2. Enabling automatic indexing

Finally, we enable the `LuceneEventListener` for the three Hibernate events that occur after changes are committed to the database.

```
<hibernate-configuration>
  ...
  <event type="post-commit-update"
    <listener
      class="org.hibernate.lucene.event.LuceneEventListener"/>
  </event>
  <event type="post-commit-insert"
    <listener
      class="org.hibernate.lucene.event.LuceneEventListener"/>
  </event>
  <event type="post-commit-delete"
    <listener
      class="org.hibernate.lucene.event.LuceneEventListener"/>
  </event>
</hibernate-configuration>
```

Appendix A. Compliance and limitations

Issue tracking numbers can be looked up in JIRA on <http://www.hibernate.org/> if you want to verify the current state.

3.1beta7 Preview (13-12-2005)

** Bug

- * [ANN-114] - NPE when SecondaryTable uses a non pk reference column in @JoinColumn
- * [ANN-115] - @Index does not work on joincolumns
- * [ANN-117] - setOrphanDelete not set causing some delete-orphan .clear() to fail
- * [ANN-123] - Support for Generics superclass
- * [ANN-124] - FIELD constant thing is wrong in the doc
- * [ANN-133] - Bytecode enhancement process adds non-transient properties to beans
- * [ANN-135] - Inconsistent range check between Range Validator class and generated DDL.
- * [ANN-136] - Validator annotations not applied to the hibernate metamodel for id properties
- * [ANN-139] - SINGLE_TABLE inheritance raise an WrongClassException under certain circumstances
- * [ANN-142] - Automatic Generation of Composite IDs - Annotation declaration fails
- * [ANN-151] - <subclass extends= broken when using AnnotationConfiguration
- * [ANN-152] - Indexes generated by the LuceneEventListener are deleted at startup (Mattias Arbin)
- * [ANN-156] - MapKey Cannot Map @Id when using @IdClass
- * [ANN-165] - @Length(min=4) ie wo max generate a varchar(Integer.MAX_VALUE)
- * [ANN-171] - Class cast exception during processing of non getter generic methods
- * [ANN-173] - ClassValidator.getInvalidValues should not depend on equals() for circularity check

** New Feature

- * [ANN-111] - add function for validating properties before bean creation
- * [ANN-116] - fetch validators from implemented interfaces
- * [ANN-125] - Validator does not preserve method hierarchy in InvalidValue[]
- * [ANN-127] - Add @Future
- * [ANN-128] - Externalize EJB3 namings to NamingStrategy

** Improvement

- * [ANN-119] - Embedded international error messages
- * [ANN-121] - Named Queries should be package level visible
- * [ANN-126] - mention usage of columnDefinition as part of @Column in docs
- * [ANN-138] - Support collections of value types with separate annotation
- * [ANN-148] - EnumType should be aware of DatabaseMetadata.storesUpperCaseIdentifiers() and co (T)
- * [ANN-149] - Do not check lazy/uninitialized fields in Validator
- * [ANN-153] - Customize the parent directory for indexes generated by LuceneEventListener (Mattias Arbin)
- * [ANN-154] - Customize Analyzer subclass for the LuceneEventListener (Mattias Arbin)
- * [ANN-168] - @FilterDef should support condition
- * [ANN-170] - Keep user order of hbm files (to ease the typedef usage)

3.1beta6 Preview (06-10-2005)

- * ANN-105 More exception handling in AnnotationConfiguration
- * ANN-109 @Index does not support join columns references
- * ANN-93 Make Hibernate Validator Serializable Friendly

3.1beta5 Preview (14-09-2005)

- * ANN-70 Lucene integration
- * ANN-13 Support for referencedColumnName referencing non PK columns for @ManyToMany
- * ANN-63 Use metadata.getUserName() when guessing Enum backing type (Scott Haug)
- * ANN-38 Finish the optional=false support
- * ANN-69 Expand the resource bundle message itself in the Validator framework
- * ANN-68 Apply validator on a particular property (Jesus Marin)
- * ANN-41 Allow field validations and validate private method (Chris Wood)
- * ANN-75 Support named (native) query parameters (from Carlos Gonzalez)
- * ANN-73 Use an eager strategy for the second join of a ManyToMany
- * ANN-74 Allow configuration artefacts (hbm, classes) loading precedence
- * ANN-79 Support collection of composite elements
- * ANN-19 Annotations should support collections of primitive and core types
- * ANN-77 Support primitive arrays

- * ANN-20 Support dotted annotation when using overriding (Alexei Akhounov)
- * ANN-55 @Proxy annotation should take proxyClass argument
- * ANN-2 Bidirectional true @OneToOne
- * ANN-80 @NotFound(action=NotFoundAction.IGNORE)
- * ANN-57 @Table ignores unique constraint in association table
- * ANN-3 Support of component inside SecondaryTable
- * ANN-87 @InheritanceJoinColumn rename is incomplete
- * ANN-81 ColumnDefinition not assigned when using @Column and @JoinColumn
- * ANN-34 Second passes binded to HbmBinder.SecondPass
- * NPE on Index and Unique constrains when column name has case inconsistency
- * ANN-86 @Index not used on properties having no @Column
- * ANN-49 Super class of Embeddable not mapped correctly (Alexei Akhounov)
- * ANN-66 Null enums don't store to database correctly
- * ANN-65 Validator ignores components (the DDL still ignores it)
- * ANN-60 NPE when @EmbeddableSuperclass has a superclass @Entity
- * ANN-90 mention usage of @Column together with @Id explicitly
- * ANN-18 Document bean-level validator mechanism

3.1beta4 Preview (04-08-2005)

- * ANN-54 EnumType fails to find the Enum in setParameterValues(Properties)
- * ANN-32 Support index creation
- * ANN-22 Hibernate 3 Annotations should support all Id generators
- * ANN-51 redeclaring id in entity subclass raises ClassCastException
- * ANN-43 @MapKey throw exception if key is id or a component subproperty
- * ANN-52 Exception when @OrderBy contains the id property or a component subproperty
- * ANN-13 Support for referencedColumnName referencing non PK columns for @ManyToOne, @OneToOne and @
- * ANN-46 Raise a warning on @Filter on subclasses
- * ANN-48 @UniqueConstraint reorders columns (Chris Wood)
- * ANN-6 enum did not worked for enums persisted in string based columns (MySQL and Oracle)
- * ANN-8 array of primitive no longer create a non null column
- * ANN-45 Proper support for @Basic byte[]
- * ANN-44 Don't mandate to list embedded superclasses
- * ANN-42 Don't mandate resultset to be defined before named native queries
- * ANN-11 More robust support for enum persistence (wider range of SQL types)
- * HBX-307 Remove @Serialized and support @Lob tagging of a serializable type

3.1beta3 (24-06-2005)

- * Rename @AssociationTable to @JoinTable
- * HBX-213 support of @IdClass
- * change targetEntity from String to Class
- * HBX-305 Support Java5 Enums
- * Add @Basic(optional=false) and Lob(optional=false)
- * HBX-284 AnnotationOverride in inheritance in conjunction with @EmbeddedSuperclass
- * HBX-304 @AttributeOverride instead of @Embedded(override=@AttributeOverride) or @EmbeddedId(...)
- * HBX-290 All collection binder exception now show the collection role
- * HBX-299 Fix test suite error on MySQL
- * HBX-302 @MapKey(name="propertyName") to map a map using a property of the associated class as a map
- * HBX-201 @Formula on properties or fields.
- * Support @EntityResult(discriminatorColumn)
- * Relax List usage as per the spec (non indexed list are defaulted to bag semantic)
- * HBX-300 enable HQL order by fragment using @javax.persistence.OrderBy
- * HBX-298 FKs on association tables are forced not null
- * HBX-297 Primitive types creates a non null constrained column if defaulted and not SINGLE_TABLE (HBX-297)
- * HBX-287 @DiscriminatorFormula
- * HBX-205 @OnDelete(action=OnDeleteAction.CASCADE) for joined subclasses and collections
- * Change @OneToOne(usePkasFk=true) into @PrimaryKeyJoinColumn
- * Rename @InheritanceJoinColumn/@InheritanceJoinColumns to @PrimaryKeyJoinColumn/@PrimaryKeyJoinColumns
- * Support @Basic(temporalType=...)
- * HBX-282 protect @ManyToOne from abusive not joined filters
- * Align with @NamedNativeQuery/@NamedNativeQueries
- * HBX-283 Better getter resolution
- * HBX-75 Implicit inheritance join columns declaration in composite PK
- * HBX-54 Explicit exception when @Id is missing
- * HBX-210 Fix NPE when the @Id was on the superclass of the root entity in conjunction with @OneToOne
- * HBX-280/HBX-157 Support @EmbeddableSuperclass

3.0beta2 Preview (26-05-2005)

- * Add the validate framework and bind it to the annotation binder.

- * HBX-199 Support @Columns and thus multi-column properties (ie composite user types)
- * HBX-206 Support @OrderBy and @Sort
- * HBX-203/HBX-81 Support Hibernate cascade strategies through @Cascade (Pablo Nussembaum)
- * HBX-47 Persist is cascaded on flush operation when using the EJB3 event listeners
- * HBX-125 Support for named native SQL queries (not Scalar results)
- * HBX-225 @Type annotation now work for @Id and @Version (Pablo Nussembaum, Emmanuel Bernard)
- * HBX-248 TABLE_PER_CLASS no longer limited to leaf entities and use union-subclass as its strategy
- * HBX-186 inheritance strategy no longer have to be defined on every entity (only on root entry)
- * HBX-53 Annotated classes can be defined in any arbitrary order
- * Support Array through @IndexColumn (Anthony Patricio)
- * HBX-216 Ignore static fields and properties
- * HBX-229/HBX-134 Filter javac generated methods that compensate type erasure aka bridge method (Rog)
- * HBX-184 Support List mappings through @IndexColumn (Matthiew Inger, Emmanuel Bernard)
- * HBX-187 Move to a CollectionBinder structure (Matthiew Inger, Emmanuel Bernard)
- * Fix of CascadeType.REMOVE

3.0beta1 Preview (07-04-2005) based on the EJB3 Early Draft 2

- * support parameters in @Type (HBX-197)
- * support @TypeDef at package and class level
- * HBX-166 support @Lob for Character[],char[], String, byte[] and Byte[] (experimental)
- * HBX-159/HBX-140 add @Filter(s) and @FilterDef(s) (Matthiew Inger, Magnus Sandberg)
- * HBX-44 @OneToOne support composite PK
- * @OneToOne is supported except for true bidirectional @OneToOne
- * Add @Cache annotation: allow to define caching on root entities and on collections (,eg @Cache(usage
- * Support @OneToMany default (ie using an association table)
- * HBX-164 insertable/updatable of @JoinColumn now work in @ManyToOne processing (Mario Ivankovits, E
- * HBX-153 @Id(generate=GeneratorType.AUTO, generator="my_potential_sequence") now work (Pablo Nussem
- * Support @ManyToMany wo @AssociationTable (ie defaults)
- * Support @ManyToMany(mappedBy)
- * Support @OneToMany(mappedBy) (no JoinColumn needed on the @OneToMany side)
- * Appropriate default value when no @JoinColumn is defined in a ManyToOne
- * rename @GeneratorTable to @GeneratedIdTable
- * rename CREATE to PERSIST, add REFRESH cascade style
- * support Mapping Defaults for Non-Relationship Fields or Properties algorithm as defined in the EJB3
- * support @Serialized
- * support @Lob for java.sql.Clob and java.sql.Blob
- * allow embedded object declaration wo @Embeddable (if @Embedded or @EmbeddedId is present in the pr
- * support for @EmbeddedId
- * rename DependentAttribute to AttributeOverride, Dependent to Embedded and DependentObject to Embed
- * support @ManyToOne in embedded objects
- * support for @NamedQuery and @NamedQueries (EJBQL)
- * move javax.ejb.* into javax.persistence.* and update copyright header

3.0alpha3 (28-02-2005)

- * HBX-116 Support for Where clause in classes and collections @Where(clause="")
- * HBX-115 Support for class proxying configuration: @Proxy(lazy=false, proxyClassName="my.Interface")
- * HBX-88 Support for hibernate type abstraction through @Type (only on basic properties for now)
- * HBX-108 Support @BatchSize(size=n) for entities and collections
- * HBX-107 implements @org.hibernate.annotations.Entity
- * HBX-103 handle abstract classes
- * HBX-83 precision & scale support for column (Bogdan Ghidireac)

3.0alpha2 (25-01-2005)

- * HBX-61 Support for @UniqueConstraint (except primaryKey=true)
- * HBX-60 Support for a proper @TableGenerator (using MultipleHiLoPerTableGenerator)
- * HBX-63 Support @GeneratorTable
- * HBX-68 Add declarative configuration of annotated classes
- * HBX-74 Rollback the HB-1315 fix: dialect no longer have to be set in hibernate.properties

Hibernate-annotations-3.0alpha1 based on the EJB3 Early Draft 1 (6.01.2005)

- * Support for EJB3 annotations:
 - @Transient
 - @Column (not primaryKey)
 - @JoinColumn (referencedColumnName - only for a reference to a PK, not primaryKey)
 - @Version
 - @Basic

- @Entity
- @Table (not uniqueConstraints)
- @AccessType
- @Id
- @CascadeType
- @FetchType
- @GeneratorType (NONE, IDENTITY, TABLE, SEQUENCE)
- @TableGenerator (with scope visibility)
- @SequenceGenerator (with scope visibility, does not support initialValue() and allocationSize())
- *not* @GeneratorTable (will have to write a new TableHiloGenerator, but it can wait)
- @ManyToOne (not optional)
- @OneToMany (Set and Collection, generics version or not, JoinColumn not guessed)
- @OneToOne
 - but not optional
 - no composite PK/FK
- @ManyToMany
- @AssociationTable (Has to be on both sides)
- @Inheritance
- @InheritanceType (has to be defined on every classes of the hierarchy for JOINED strategy, not very clear about the TABLE_PER_CLASS strategy)
- @DiscriminatorColumn
- @DiscriminatorType
- @InheritanceJoinColumn
- @InheritanceJoinColumns
 - this annotation for Composite PK Entities has to be explicit, I do not respect the implicit semantics
- @SecondaryTable (@OneToMany @JoinColumn(secondaryTable="..." does not work yet due to H3 core issues)
- @SecondaryTables
 - this annotation for Composite PK Entities has to be explicit, I do not respect the implicit semantics
- @DependentObject
- @Dependent
- @DependentAttribute (only for basic properties as per the spec)
- @Id in conjunction with @DependentObject (composite primary keys)
- @JoinColumns in conjunction with @ManyToOne, @OneToMany, @ManyToMany
 - note that the composite FK columns have to be in the same table (no != secondary tables). This is not supported yet.

Still missing or incomplete features compared to the EJB3 spec

-
- support for initialValue and allocationSize in @SequenceGenerator (HBX-59)