



1

2

3

OASIS Service Provisioning Markup Language (SPML) v2 - DSML v2 Profile

4

5

OASIS Standard 2006 April 1

6

Document identifier: `pstc-spml2-dsml-profile-os.pdf`

7

Location: <http://www.oasis-open.org/committees/provision/docs/>

8

Send comments to: pstc-comment@lists.oasis-open.org

9

Editor:

10

Jeff Bohren, BMC (Jeff_Bohren@bmc.com)

11

12

Contributors:

13

Robert Boucher, CA

14

Doron Cohen, BMC

15

Gary Cole, Sun Microsystems

16

Cal Collingham, CA

17

Rami Elron, BMC

18

Marco Fanti, Thor Technologies

19

Ian Glazer, IBM

20

James Hu, HP

21

Ron Jacobsen, CA

22

Jeff Larson, Sun Microsystems

23

Hal Lockhart, BEA

24

Prateek Mishra, Oracle Corporation

25

Martin Raepfle, SAP

26

Darran Rolls, Sun Microsystems

27

Kent Spaulding, Sun Microsystems

28

Gavenraj Sodhi, CA

29

Cory Williams, IBM

30

Gerry Woods, SOA Software

31

32

Abstract:

33

This specification defines usage of DSML v2 as a data model (profile) for SPML v2.

34

Status:

35 This is an OASIS Standard document produced by the Provisioning Services Technical
36 Committee. It was approved by the OASIS membership on 1 April 2006.

37 If you are on the provision list for committee members, send comments there. If you are not
38 on that list, subscribe to the provision-comment@lists.oasis-open.org list and send
39 comments there. To subscribe, send an email message to [provision-comment-](mailto:provision-comment-request@lists.oasis-open.org)
40 [request@lists.oasis-open.org](mailto:provision-comment-request@lists.oasis-open.org) with the word "subscribe" as the body of the message.

41 Copyright (C) OASIS Open 2006. All Rights Reserved.

42	Table of contents	
43	1. Introduction (non-normative)	4
44	1.1. Concepts	4
45	1.1.1. DSML Protocol	4
46	1.1.2. Schema	4
47	1.2. Terminology	4
48	2. Notation	4
49	3. Overview (non-normative)	5
50	3.1. DSML PSOs	5
51	3.1.1. PSO Identifier	6
52	3.1.2. PSO Data	6
53	3.2. Schema	6
54	3.3. Core Operations	6
55	3.3.1. Add Request	6
56	3.3.2. Add Response	7
57	3.3.3. Modify Request	7
58	3.3.4. Modify Response	8
59	3.3.5. Delete Request	8
60	3.3.6. Lookup Request	8
61	3.3.7. Lookup Response	8
62	3.4. Search Operations	8
63	3.4.1. Search Request	9
64	3.4.2. Search Response	9
65	4. Specification (Normative)	10
66	4.1. Namespaces	10
67	4.2. Core Capability	10
68	4.2.1. Element <spml:data>	10
69	4.2.2. Element <spml:modification>	10
70	4.2.3. Element <spml:schema>	10
71	4.2.4. Element <supportedSchemaEntity>	10
72	4.3. Search Capability	11
73	4.3.1. Element <spmlsearch:query>	11
74	4.4. DSML Profile Schema	11
75	4.4.1. Element <spml:dsml:schema>	11
76	4.4.2. Element <spml:dsml:objectClassDefinition>	11
77	4.4.3. Element <spml:dsml:attributeDefinition>	11

78	Appendix A. References	12
79	Appendix B. Acknowledgments	14
80	Appendix C. Notices	15
81		

82 **1. Introduction (non-normative)**

83 **1.1. Concepts**

84 SPML Version 2 (SPMLv2) defines a core protocol **[SPMLv2]** over which different data models can
85 be used to define the actual provisioning data. The combination of a data model with the SPML
86 core specification is referred to as a profile. The use of SPML requires that a specific profile is
87 used, although the choice of which profile is used to negotiated out-of-band by the participating
88 parties.

89 This document describes the use of the DSML protocol as a data model for SPML based
90 provisioning. This profile is optional.

91 **1.1.1. DSML Protocol**

92 The DSML v2 protocol **[DSMLV2]** was designed to perform LDAP type operations using web
93 services. The DSML V2 protocol defines synchronous request/response semantics and a data
94 model based on attribute/value pairs. DSML V2 does not define an attribute/value pairs schema
95 mechanism.

96 **1.1.2. Schema**

97 The DSML v2 standard does not define a schema mechanism. A schema mechanism is defined as
98 part of this binding.

99 **1.2. Terminology**

100 Within this document:

- 101 - The term “requestor” always refers to a [Requesting Authority \(RA\)](#).
- 102 - The term “provider” always refers to a [Provisioning Service Provider \(PSP\)](#).
- 103 - The term “target” always refers to a [Provisioning Service Target \(PST\)](#).
- 104 - The term “object” (unless otherwise qualified) refers to a [Provisioning Service Object \(PSO\)](#).
- 105 - The term “client” (unless otherwise qualified) refers to a [Requesting Authority \(RA\)](#).
- 106 - The term “server” (unless otherwise qualified) refers to a [Provisioning Service Provider \(PSP\)](#).

107 **2. Notation**

108 This specification contains schema conforming to W3C XML Schema and normative text to
109 describe the syntax and semantics of XML-encoded policy statements.

110 The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD",
 111 "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this specification are to be
 112 interpreted as described in IETF RFC 2119 [RFC2119]

113 *"they MUST only be used where it is actually required for interoperation or to limit*
 114 *behavior which has potential for causing harm (e.g., limiting retransmissions)"*

115 These keywords are thus capitalized when used to unambiguously specify requirements over
 116 protocol and application features and behavior that affect the interoperability and security of
 117 implementations. When these words are not capitalized, they are meant in their natural-language
 118 sense.

119 This specification uses the following typographical conventions in text:

Format	Description	Indicates
attributeName	monospace font with <i>first letter lower-cased</i>	The name of an XML <i>attribute</i> .
SPMLElementName	monospace font with <i>first letter capitalized</i>	The name of an XML <i>element</i> that is defined as part of SPMLv2.
ns:ForeignElementName	monospace font with <i>namespace prefix</i>	The name of an XML element that is <i>defined by another specification</i> .
<SPMLElement>	monospace font <i>surrounded by <></i>	<i>An instance of an XML element</i> that is defined as part of SPMLv2.
<ns:ForeignElement>	monospace font with <i>namespace prefix</i> <i>surrounded by <></i>	An instance of an XML element that is <i>defined by another specification</i> .

120 Terms in ***italic bold-face*** are intended to have the meaning defined in the Glossary.

121 Listings of SPML schemas appear like this.

122

123 Example code listings appear like this.

124 Conventional XML namespace prefixes are used throughout the listings in this specification to
 125 stand for their respective namespaces as follows, whether or not a namespace declaration is
 126 present in the example:

127 - The prefix `dsml` : stands for the Directory Services Markup Language namespace [DSML].

128 - The prefix `saml` : stands for the SAML assertion namespace [SAML].

129 - The prefix `ds` : stands for the W3C XML Signature namespace [DS].

130 - The prefix `xsd` : stands for the W3C XML Schema namespace [XS].

131 3. Overview (non-normative)

132 3.1. DSML PSOs

133 A PSO is represented in this binding by a set of attribute/values pairs that is associated with a
 134 target-unique identifier. All PSOs are categorized by one or more object classes. The object class
 135 for a given PSO is denoted by an attribute named with the reserved name of "objectclass".

136 3.1.1. PSO Identifier

137 The PSO Identifier may be an X.509 Distinguished Name (DN), or any identifier that is unique for
138 the target..

```
139 <spml:pso xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
140   <spml:psoid ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com"/>  
141 </spml:pso>
```

142 3.1.2. PSO Data

143 The PSO Data element contains dsml:attr elements, as defined in [DSML]. Additional data may be
144 included via the Open Content Model.

```
145 <spml:pso xmlns:spml="urn:oasis:names:tc:SPML:2:0" >  
146   <spml:data>  
147     <attr name="cn" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
148       <value>John Doe</value>  
149     </attr>  
150     <attr name="uid">  
151       <value>jdoe</value>  
152     </attr>  
153     <attr name="email" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
154       <value>jdoe@acme.com</value>  
155     </attr>  
156     <attr name="objectclass" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
157       <value>user</value>  
158     </attr>  
159   </spml:data>  
160 </spml:pso>
```

161 3.2. Schema

162 The schema defines the allowed attributes and object classes.

```
163 <spml:schema xmlns:spml="urn:oasis:names:tc:SPML:2:0"  
164   xmlns:spml:dsml="urn:oasis:names:tc:SPML:2:0:DSML">  
165   <spml:dsml:schema>  
166     <spml:dsml:attributeDefinition name="cn" description="Common Name" />  
167     <spml:dsml:attributeDefinition name="uid" description="User ID" />  
168     <spml:dsml:attributeDefinition name="email" description="Email Address" />  
169     <spml:dsml:objectClassDefinition name="person">  
170       <spml:dsml:memberAttributes>  
171         <spml:dsml:memberAttributes name="cn" required="true" />  
172         <spml:dsml:memberAttributes name="uid"/>  
173         <spml:dsml:memberAttributes name="email"/>  
174       </spml:dsml:memberAttributes>  
175     </spml:dsml:objectClassDefinition>  
176   </spml:dsml:schema>  
177 </spml:schema>
```

178 3.3. Core Operations

179 3.3.1. Add Request

180 The Add Request creates PSOs. The Add Request must contain a <data> element that contains
181 DSML v2 <attr> elements that define the new PSO. The Add Request may also pass a PSO

182 Identifier (<psoid> element), a container PSO ID (<containerID> element), or a target ID
183 (<targetID> element). If a PSO identifier is not defined in the Add Request, the new PSO Identifier
184 must be returned in the Add Response.

```
185 <spml:addRequest xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
186   <spml:containerID ID="OU=accounting,DC=acme.com" targetID="acme.com" />  
187   <spml:data>  
188     <attr name="CN" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
189       <value> John Doe </value>  
190     </attr>  
191     <attr name="uid" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
192       <value>jdoe</value>  
193     </attr>  
194     <attr name="objectclass" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
195       <value>user</value>  
196     </attr>  
197   </spml:data>  
198 </spml:addRequest>
```

199 **3.3.2. Add Response**

200 The Add Response message will contain the new PSO ID (unless it was specified in the Add
201 Request). If the creation of the new PSO resulted in attributes being adding or modified in the new
202 PSO, the entire PSO Data should be returned in the response.

```
203 <spml:addResponse status="spml:success" xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
204   <spml:psoid ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
205   <spml:data>  
206     <attr name="CN" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
207       <value> John Doe </value>  
208     </attr>  
209     <attr name="uid" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
210       <value>jdoe</value>  
211     </attr>  
212     <attr name="email" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
213       <value>jdoe@acme.com</value>  
214     </attr>  
215     <attr name="objectclass" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
216       <value>user</value>  
217     </attr>  
218   </spml:data>  
219 </spml:addResponse>
```

220 **3.3.3. Modify Request**

221 The Modify Request modifies the specified PSO. The Modify Request must always contain the
222 PSO Identifier.

```
223 <spml:modifyRequest xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
224   <spml:psoid ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
225   <spml:modification>  
226     <modification name="CN" operation="replace"  
227     xmlns="urn:oasis:names:tc:DSML:2:0:core">  
228       <value>Jane Doe</value>  
229     </modification>  
230   </spml:modification>  
231 </spml:modifyRequest >
```

232 **3.3.4. Modify Response**

233 If the Modify Request causes the PSO ID to change, then the Modify Response must contain the
234 new PSO ID.

```
235 <spml:modifyResponse status="spml:success"  
236 xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
237   <spml:psId ID="CN=Jane Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
238 </spml:modifyResponse>
```

239 **3.3.5. Delete Request**

240 The Delete Request deletes a specified PSO.

```
241 <spml:deleteRequest xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
242   <spml:psId ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
243 </spml:deleteRequest >
```

244

245 **3.3.6. Lookup Request**

246 The Lookup Request is used to retrieve the data for a specified PSO.

```
247 <spml:lookupRequest xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
248   <spml:psId ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
249 </spml:lookupRequest>
```

250 **3.3.7. Lookup Response**

251 The Lookup Response contains the retrieved PSO data.

```
252 <spml:lookupResponse status="spml:success"  
253 xmlns:spml="urn:oasis:names:tc:SPML:2:0">  
254   <spml:psId ID="CN=John Doe,OU=accounting,DC=acme.com" targetID="acme.com" />  
255   <spml:data>  
256     <attr name="CN" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
257       <value> John Doe </value>  
258     </attr>  
259     <attr name="uid" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
260       <value>jdoe</value>  
261     </attr>  
262     <attr name="email" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
263       <value>jdoe@acme.com</value>  
264     </attr>  
265     <attr name="objectclass" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
266       <value>user</value>  
267     </attr>  
268   </spml:data>  
269 </spml:lookupResponse>
```

270 **3.4. Search Operations**

271 If the Search Capability is supported, the DSML filters and attribute declarations should be used to
272 scope the results of the search.

273 3.4.1. Search Request

274 The search request can specify DSML filters and attribute declarations, as defined in [DSML].

275

```
276 <spmlsearch:searchRequest xmlns:spml="urn:oasis:names:tc:SPML:2:0"  
277 xmlns:spmlsearch="urn:oasis:names:tc:SPML:2:0:search">  
278   <spmlsearch:query scope = "spmlsearch:oneLevel">  
279     <spml:basePSOID ID="CN=John Doe,OU=accounting,DC=acme.com"  
280     targetID="acme.com" />  
281     <filter xmlns="urn:oasis:names:tc:DSML:2:0:core">  
282       <substrings name = "cn">  
283         <initial>John</initial>  
284       </substrings>  
285     </filter>  
286     <attributes xmlns="urn:oasis:names:tc:DSML:2:0:core">  
287       <attribute name = "cn" />  
288       <attribute name = "email" />  
289     </attributes>  
290   </spmlsearch:query>  
291 </spmlsearch:searchRequest>
```

292

293 3.4.2. Search Response

294

```
295 <spmlsearch:searchResponse status="spml:success"  
296 xmlns:spml="urn:oasis:names:tc:SPML:2:0"  
297 xmlns:spmlsearch="urn:oasis:names:tc:SPML:2:0:search">  
298   <spml:pso>  
299     <spml:psoId ID="CN=John Doe,OU=accounting,DC=acme.com"  
300     targetID="acme.com"/>  
301     <spml:data>  
302       <attr name="cn" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
303         <value>John Doe</value>  
304       </attr>  
305       <attr name="email" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
306         <value>jdoe@acme.com</value>  
307       </attr>  
308     </spml:data>  
309   </spml:pso>  
310   <spml:pso>  
311     <spml:psoId ID="CN=John Smith,OU=accounting,DC=acme.com"  
312     targetID="acme.com"/>  
313     <spml:data>  
314       <attr name="cn" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
315         <value>John Smith</value>  
316       </attr>  
317       <attr name="email" xmlns="urn:oasis:names:tc:DSML:2:0:core">  
318         <value>jsmith@acme.com</value>  
319       </attr>  
320     </spml:data>  
321   </spml:pso>  
322 </spmlsearch:searchResponse>
```

323 4. Specification (Normative)

324 4.1. Namespaces

325 The DSMLv2 Profile uses the DSML v2 namespace which is defined as:

```
326 urn:oasis:names:tc:DSML:2:0:core
```

327 The specification uses the prefix dsml: to refer to this namespace.

328 The DSMLv2 Profile defines some elements that are specific to the profile. The namespace for the
329 profile itself is defined as:

```
330 urn:oasis:names:tc:SPML:2:0:DSML
```

331 The specification uses the prefix spml: to refer to this namespace.

332 4.2. Core Capability

333 4.2.1. Element <spml:data>

334 The <spml:data> element MUST contain zero or many <dsml:attr> elements.

335 4.2.2. Element <spml:modification>

336 The <spml:modification> element MUST contain zero or many <dsml:modification> elements. The
337 “modificationType” on the <spml:modification> MUST NOT be specified since the
338 <dsml:modification> defines the modification type.

339 4.2.3. Element <spml:schema>

340 If the schema is defined in-band, the <spml:schema> element MUST contain one or more
341 <spml:dsml:schema> elements. If the schema is defined out-of-band, the “ref” attribute on the
342 <spml:schema> element MUST be set to the URN of the referenced schema.

343 If only a subset of the object classes defined in the schema are supported for the target, then the
344 <spml:schema> element MUST include <spml:supportedSchemaEntity>. If no
345 <spml:supportedSchemaEntity> are defined in the <spml:schema> element, then it is assumed all
346 object classes are supported by the target.

347 4.2.4. Element <supportedSchemaEntity>

348 The “entityName” attribute on the <spml:supportedSchemaEntity> element MUST refer only to
349 object classes defined in the referenced schema. All attributes on the referenced object classes are
350 assumed to be supported.

351 **4.3. Search Capability**

352 **4.3.1. Element <spmlsearch:query>**

353 The <spmlsearch:query> element MAY contain <dsml:filter> and <dsml:attributes> to filter the
354 results of the search.

355 **4.4. DSML Profile Schema**

356 **4.4.1. Element <spmldsml:schema>**

357 The <spmldsml:schema> element defines the DSML schema for the target. The
358 <spmldsml:schema> element contains zero or more <spmldsml:objectClassDefinition> elements
359 and zero or more <spmldsml:attributeDefinition> elements.

360 **4.4.2. Element <spmldsml:objectClassDefinition>**

361 The <spmldsml:objectClassDefinition> element defines DSML v2 object classes supported by the
362 target. The <spmldsml:objectClassDefinition> element contains zero or more
363 <spmldsml:memberAttributes> elements which define the attributes that may be included on
364 objects of the specified object class. The <spmldsml:objectClassDefinition> element contains zero
365 or more <spmldsml:superiorClasses> which define the superior object classes to the specified
366 object class.

367 **4.4.3. Element <spmldsml:attributeDefinition>**

368 The <spmldsml:attributeDefinition> element defines DSML v2 attributes supported by the target.
369 The <spmldsml:attributeDefinition> element has the following attributes:

- 370 • description – textual description of the attribute
- 371 • multivalued – true if the attribute is multivalued, false if it is single valued
- 372 • type – attribute syntax
- 373 • name – attribute name (e.g. “cn”)

374 .

375 Appendix A. References

376

- 377 **[AES]** National Institute of Standards and Technology (NIST), FIPS-197:
378 Advanced Encryption Standard,
379 <http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf>, National
380 Institute of Standards and Technology (NIST)
- 381 **[ARCHIVE-1]** OASIS Provisioning Services Technical Committee, email archive,
382 [http://www.oasis-](http://www.oasis-open.org/apps/org/workgroup/provision/email/archives/index.html)
383 [open.org/apps/org/workgroup/provision/email/archives/index.html](http://www.oasis-open.org/apps/org/workgroup/provision/email/archives/index.html),
384 OASIS PS-TC
- 385 **[DS]** IETF/W3C, *W3C XML Signatures*, <http://www.w3.org/Signature/>,
386 W3C/IETF
- 387 **[DSML]** OASIS Directory Services Markup Standard, *DSML V2.0 Specification*,
388 <http://www.oasis-open.org/specs/index.php#dsmlv2>, OASIS DSML
389 Standard
- 390 **[GLOSSARY]** OASIS Provisioning Services TC, *Glossary of Terms*, [http://www.oasis-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php)
391 [open.org/apps/org/workgroup/provision/download.php](http://www.oasis-open.org/apps/org/workgroup/provision/download.php), OASIS PS-TC
- 392 **[RFC 2119]** S. Bradner., *Key words for use in RFCs to Indicate Requirement Levels*,
393 <http://www.ietf.org/rfc/rfc2119.txt>, IETF
- 394 **[RFC 2246]** T. Dierks and C. Allen, *The TLS Protocol*,
395 <http://www.ietf.org/rfc/rfc2246.txt>, IETF
- 396 **[SAML]** OASIS Security Services TC, [http://www.oasis-](http://www.oasis-open.org/committees/tc_home.php?wg_abbrev=security)
397 [open.org/committees/tc_home.php?wg_abbrev=security](http://www.oasis-open.org/committees/tc_home.php?wg_abbrev=security), OASIS SS-
398 TC
- 399 **[SOAP]** W3C XML Protocol Working Group, <http://www.w3.org/2000/xp/Group/>
- 400 **[SPML-Bind]** OASIS Provisioning Services TC, SPML V1.0 Protocol Bindings,
401 [http://www.oasis-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/1816/draft-pstc-bindings-03.doc)
402 [open.org/apps/org/workgroup/provision/download.php/1816/draft-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/1816/draft-pstc-bindings-03.doc)
403 [pstc-bindings-03.doc](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/1816/draft-pstc-bindings-03.doc), OASIS PS-TC
- 404 **[SPML-REQ]** OASIS Provisioning Services Technical Committee, *Requirements*,
405 [http://www.oasis-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/2277/draft-pstc-requirements-01.doc)
406 [open.org/apps/org/workgroup/provision/download.php/2277/draft-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/2277/draft-pstc-requirements-01.doc)
407 [pstc-requirements-01.doc](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/2277/draft-pstc-requirements-01.doc), OASIS PS-TC
- 408 **[SPML-UC]** OASIS Provisioning Services Technical Committee, *SPML V1.0 Use*
409 *Cases*, [http://www.oasis-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/988/draft-spml-use-cases-05.doc)
410 [open.org/apps/org/workgroup/provision/download.php/988/draft-](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/988/draft-spml-use-cases-05.doc)
411 [spml-use-cases-05.doc](http://www.oasis-open.org/apps/org/workgroup/provision/download.php/988/draft-spml-use-cases-05.doc), OASIS PS-TC
- 412 **[SPMLv2-Profile-DSML]** OASIS Provisioning Services Technical Committee, SPMLv2
413 DSMLv2 Profile, OASIS PS-TC
- 414 **[SPMLv2-Profile-XSD]** OASIS Provisioning Services Technical Committee, SPML V2
415 XSD Profile, OASIS PS-TC
- 416 **[SPMLv2-REQ]** OASIS Provisioning Services Technical Committee, *Requirements*, OASIS
417 PS-TC

447 **Appendix B. Acknowledgments**

448 The following individuals were voting members of the Provisioning Services committee at the time
449 that this version of the specification was issued:

450 Jeff Bohren, BMC
451 Robert Boucher, CA
452 Gary Cole, Sun Microsystems
453 Rami Elron, BMC
454 Marco Fanti, Thor Technologies
455 James Hu, HP
456 Martin Raeppele, SAP
457 Gavenraj Sodhi, CA
458 Kent Spaulding, Sun Microsystems
459
460
461
462

463 Appendix C. Notices

464 OASIS takes no position regarding the validity or scope of any intellectual property or other rights
465 that might be claimed to pertain to the implementation or use of the technology described in this
466 document or the extent to which any license under such rights might or might not be available;
467 neither does it represent that it has made any effort to identify any such rights. Information on
468 OASIS's procedures with respect to rights in OASIS specifications can be found at the OASIS
469 website. Copies of claims of rights made available for publication and any assurances of licenses to
470 be made available, or the result of an attempt made to obtain a general license or permission for
471 the use of such proprietary rights by implementers or users of this specification, can be obtained
472 from the OASIS Executive Director.

473 OASIS has been notified of intellectual property rights claimed in regard to some or all of the
474 contents of this specification. For more information consult the online list of claimed rights.

475 OASIS invites any interested party to bring to its attention any copyrights, patents or patent
476 applications, or other proprietary rights which may cover technology that may be required to
477 implement this specification. Please address the information to the OASIS Executive Director.

478 Copyright (C) OASIS Open 2006. All Rights Reserved.

479 This document and translations of it may be copied and furnished to others, and derivative works
480 that comment on or otherwise explain it or assist in its implementation may be prepared, copied,
481 published and distributed, in whole or in part, without restriction of any kind, provided that the above
482 copyright notice and this paragraph are included on all such copies and derivative works. However,
483 this document itself may not be modified in any way, such as by removing the copyright notice or
484 references to OASIS, except as needed for the purpose of developing OASIS specifications, in
485 which case the procedures for copyrights defined in the OASIS Intellectual Property Rights
486 document must be followed, or as required to translate it into languages other than English.

487 The limited permissions granted above are perpetual and will not be revoked by OASIS or its
488 successors or assigns.

489 This document and the information contained herein is provided on an "AS IS" basis and OASIS
490 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO
491 ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY
492 RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A
493 PARTICULAR PURPOSE.